Elkay Outdoor ezH2O Middle Bottle Filling Station Tri-Level Pedestal Non-Filtered Non-Refrigerated

Model LK4430BF1M

PRODUCT SPECIFICATIONS

Elkay Outdoor ezH2O® Middle Bottle Filling Station Tri-Level Pedestal Non-Filtered Non-Refrigerated. Features shall include 316 Stainless, Heavy Duty Vandal Resistant, Laminar Flow. Furnished with Vandal Resistant bubbler. Mechanical Front Bubbler Button activation. Product shall be Floor Mount/Freestanding, for Outdoor applications, serving 3 station(s).

Special Features:	316 Stainless, Heavy Duty Vandal		
Special realures.			
	Resistant, Laminar Flow		
Finish:	Black (BK), Blue (BLU),		
	Evergreen (EVG), Gray (GRY),		
	Powder Coat (12 Color Options)		
Power:	No Electrical Required		
Bubbler Style:	Vandal Resistant		
Activation by:	Mechanical Front Bubbler Button		
Mounting Type:	Floor Mount/Freestanding		
Chilling Capacity:	Non-refrigerated		
Dimensions (L x W x H):	14" x 48" x 55-1/8"		
Approx. Shipping Weight:	215 lbs.		
Installation Location:	Outdoor		
No. of Stations Served:	3		

**When used in non-temperature controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.

Special Note: Bottle Filler Stations 1 (Mid), Bubbler Stations 2 (Upper-Low), Choose from 12 color options

- Mechanically-Activated bubbler continues to supply water in event of service disruptions.
- Laminar flow provides clean fill with minimal splash.
- Base material constructed from marine-grade 316 stainless steel provides the ultimate corrosion protection from even the most corrosive elements.



Included with Product: Outdoor Bottle Filler Ships in one box.

A Century of Tradition and Quality.

For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.

PRODUCT COMPLIANCE

ADA & ICC A117.1 ASME A112.19.3/CSA B45.4 Buy American Act GreenSpec® NSF/ANSI 61 & 372 (lead free)



Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty. Warranty (PDF)

PART:	QTY:
PROJECT:	
NOTES:	
APPROVAL:	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



Elkay Outdoor ezH2O Middle Bottle Filling Station Tri-Level Pedestal Non-Filtered Non-Refrigerated

Model LK4430BF1M

Optional Accessories		
LK4471LHB	Locking Hose Bib Spec Sheet (PDF)	
<u>97890C</u>	Accessory - Direct Bury Adaptor Spec Sheet (PDF)	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

OPERATING PRESSURES: Supply water 20 – 105 psi maximum



MOUNTING INSTRUCTIONS and PLUMBING CONNECTIONS


Provide solid, well-drained surface to mount pedestal fountain (concrete pad recommended) with adequate support (300 lb. load minimum). (6) 3/8" minimum fasteners (not included) should be attached firmly to mounting surface in order to secure unit. (Refer to rough-in diagram)

Locate and install plumbing through ground as required


NOTE: Unit is not furnished with service valve.

Position pedestal over plumbing and secure base to fasteners. Remove access panels and connect supply and water lines. Turn on water supply and check for leaks. Reassemble access panels to pedestal.

Trap and service stop not included.



FRONT VIEW SIDE VIEW **BACK VIEW**



- A = 3/8" O.D. Unplated copper tube connect. Shut off valve by others.
- B = Access panel(8" x 10")
- C = Removable bottom cover.

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.