

## Elkay ezH2O Vandal-Resistant Bottle Filling Station & Single Cooler Non-Filtered Non-Refrigerated Stainless

**Model VRCDWSK** 

## PRODUCT SPECIFICATIONS

Elkay ezH2O® Vandal-Resistant Bottle Filling Station & Single Cooler Non-Filtered Non-Refrigerated Stainless. Features shall include Green Ticker™, Laminar Flow, Real Drain, Vandal Resistant. Furnished with Vandal Resistant bubbler. Electronic Bottle Filler Button with Mechanical Front Bubbler Button activation. Product shall be Wall Mount (On Wall), for Indoor + Outdoor applications, serving 1 station(s). Unit shall be certified to UL 399 and CAN/CSA C22.2 No. 120.

Special Features:	Green Ticker™, Laminar Flow, Real Drain, Vandal Resistant		
Finish:	Stainless Steel		
Power:	115V/60Hz		
Bubbler Style:	Vandal Resistant		
Activation by:	Electronic Bottle Filler Button with Mechanical Front Bubbler Button		
Mounting Type:	Wall Mount (On Wall)		
Chilling Capacity:	Non-refrigerated		
Full Load Amps	1		
Rated Watts:	15		
Dimensions (L x W x H):	18" x 18-5/8" x 38-13/16"		
Approx. Shipping Weight:	86 lbs.		
Installation Location:	Indoor + Outdoor		
No. of Stations Served:	1		

\*\*When used in non-temperature controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.

- Mechanically-Activated bubbler continues to supply water in event of service disruptions.
- Green Ticker: Informs user of number of 20 oz. plastic water bottles saved from waste.
- Laminar flow provides clean fill with minimal splash.
- Real Drain System eliminates standing water.



Included with Product: Water

Water Cooler (VRCDWS), Bottle Filler (VRCWS)

### **▼** Ships in multiple boxes.

A Century of Tradition and Quality.
For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.

### PRODUCT COMPLIANCE

ADA & ICC A117.1

ASME A112.19.3/CSA B45.4

Buy American Act

CAN/CSA C22.2 No. 120

GreenSpec®

NSF/ANSI 61 & 372 (lead free)

UL 399







Installation Instructions (PDF) - 98980C

Electrical components and water system are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.

Warranty (PDF)

PART:	QTY:
PROJECT:	
CONTACT:	
DATE:	
NOTES:	
APPROVAL:	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



## Elkay ezH2O Vandal-Resistant Bottle Filling Station & Single Cooler Non-Filtered Non-Refrigerated Stainless

Model VRCDWSK

Optional Accessories		
<u>EWF3000</u>	Elkay Universal Filtration Kit (3000-Gallon)  Spec Sheet (PDF)	
<u>98324C</u>	Cane Apron for HAC HVR EMABF & VRC Models (Stainless)  Spec Sheet (PDF)	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

# Elkay ezH2O Vandal-Resistant Bottle Filling Station & Single Cooler Non-Filtered Non-Refrigerated Stainless

**Model VRCDWSK** 

release tube

#### IMPORTANT! **INSTALLER PLEASE NOTE:**

This water cooler has been designed and built to provide water to the user which has not been altered by materials in the cooler waterways. The grounding of electrical equipment such as telephone, computer, etc. to water lines is a common procedure. The grounding may be in the building but may also occur away from the building. This grounding can cause electrical feedback into a water cooler creating an electrolysis which creates a metallic taste or causes an increase in the metal content of the water. This condition is avoidable by installing the cooler using the proper materials as shown

#### NOTICE

This water cooler must be connected to the water supply using a dielectric coupling. The cooler is furnished with a non-metallic strainer which meets this requirement. The drain trap which is provided by the installer should also be plastic to completely isolate the cooler from the building plumbing system.

Bottle filler unit on bracket attached to wall by 6 holes (as shown). Water and electrical

will connect through pre-punched hole in basin.

These products are designed to operate on 20 psi to 105 psi supply line pressure

Simply push in |Tube is secured |Push in collet to tube to attach in position release tube . Pushing tube in before pulling it out helps to

OPERATION OF QUICK CONNECT FITTINGS

1/4" O.D. tube 3/8" O.D. Tube connect Building water water inlet to cold water supply inlet cooler 40 Servicé stop NOTE: Waterflow (Not furnished) direction

18-5/8" 16-5/16 (414mm) (472mm) Ø 5/16" 5-1/8" (8mm) — MOUNTING (178mm) (178mm) (131mm) HOLES (3PL) 51-1/8" (1298mm) HANGER 18-1/2" BRACKET (470mm) 2-5/8 1/4" 1/2" (6mm x 13mm) OBROUND HOLE (5PL) (66mm) 48' 1-1/4" 1-1/4" (1219mm) (32mm) <sub>I</sub> (32mm) E e \_4-9/16" (116mm) E 33-1/16" (840mm) ORIFICE 49-1/2" (1257mm) E HEIGHT + 🗍 (203mm) 3/4" + (18mm) 2-1/2" 7-1/4" (185mm) (64mm) 31-15/16" (811mm) D. 31' (788mm) HEIGHT (635mm) 2-7/16 (63mm) 1-1/2" 21-3/8 (686mm) (38mm) 3-1/2 (543mm) 2-9/16" ADA REQUIREMENT (89mm) 4-1/2 6-1/4" (65mm) 18-3/8" 13-7/8" (352mm) (159mm)(114mm) 12-5/16" (467mm) 10" (313mm)6-3/4 (127mm) (254mm) (171mm) FINISHED FLOOR FINISHED FLOOR REDUCE HEIGHT BY 3" FOR INSTALLATION OF CHILDREN'S ADA COOLER

A = Recommended Water Supply location. Shut-off Valve (not furnished) to accept 3/8" O.D. unplated copper tube. Up to 3" (76mm) maximum out from wall. B = Recommended Waste Outlet location. To accommodate 1-1/4" nominal drain. Drain stub 2" (51mm) out from wall.

C = 1-1/4" Trap (not furnished)

D = Electrical Supply (3) Wire Recessed Box Duplex Outlet.

E = Insure proper ventilation by maintaining 6" (152mm) minimum clearance from cabinet louvers to wall.
F = 7/16" (11mm) Bolt Holes for fastening to wall.

Note: New Installations Must Use Ground Fault Circuit Interrupter (GFCI). It is highly recommended that the circuit be dedicated and the load protection be sized for 20 amps

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.