

Elkay Cooler Wall Mount Non-Filtered Refrigerated 8 GPH Light Gray Granite Model EWA8L1Z

PRODUCT SPECIFICATIONS

Elkay Cooler Wall Mount Non-Filtered Refrigerated 8 GPH Light Gray Granite. Chilling Capacity of 8.0 GPH (gallons per hour) of 50° F drinking water, based on 80° F inlet water and 90° F ambient, per ASHRAE 18 testing. Furnished with Flexi-Guard ® Safety Bubbler. Mechanical Top Bubbler Button activation. Product shall be Wall Mount (On Wall), for Indoor applications, serving 1 station(s). Unit shall be certified to UL 399 and CAN/CSA C22.2 No. 120. Unit shall be lead-free design which is certified to NSF/ANSI 61 & 372 (lead free) and meets Federal and State low-lead requirements.

Finish:	Light Gray Granite	
Power:	115V/60Hz	
Bubbler Style:	Flexi-Guard ® Safety Bubbler	
Activation by:	Mechanical Top Bubbler Button	
Mounting Type:	Wall Mount (On Wall)	
Chilling Capacity*:	8.0 GPH	
Full Load Amps	5	
Rated Watts:	370	
Dimensions (L x W x H):	18" x 14-1/2" x 29-1/2"	
Approx. Shipping Weight:	60 lbs.	
Installation Location:	Indoor	
No. of Stations Served:	1	
*Deserved and 0.0% E indictionation & 0.0% E combined aim terms for E.0% E chilled		

*Based on 80° F inlet water & 90° F ambient air temp for 50° F chilled drinking water.

Mechanically-Activated bubbler continues to supply water in event of service disruptions.

COOLING SYSTEM

- Compressor: Hermetically-sealed, reciprocating type, single phase. Sealed-in lifetime lubrication.
- Condenser: Fan cooled, copper tube with aluminum fins. Fan motor is permanently lubricated.
- Cooling Unit: Combination tube-tank type. Continuous copper tubing with is fully insulated with EPS foam that meets UL requirements for self-extinguishing material.
- Refrigerant Control: Refrigerant R-134a is controlled by accurately calibrated capillary tube.
- Temperature Control: Easily accessible enclosed adjustable thermostat is factory preset. Requires no adjustment other than for altitude requirements.



Water Cooler

Included with Product: Ships in one box.

AMERICAN PRIDE. A LIFETIME TRADITION. Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and operated company, providing thousands of jobs that support our families and communities.

PRODUCT COMPLIANCE

ASME A112.19.3/CSA B45.4

Buy American Act

CAN/CSA C22.2 No. 120

NSF/ANSI 61 & 372 (lead free) UL 399



Installation Instructions (PDF)

5 Year Limited Warranty on the refrigeration system of the unit. Electrical components and water system are warranted for 12 months from date of installation. **Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.**

Warranty (PDF)

PART:	_QTY:
PROJECT:	
CONTACT:	
DATE:	
NOTES:	
APPROVAL:	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.





Elkay Cooler Wall Mount Non-Filtered Refrigerated 8 GPH Light Gray Granite **Model EWA8L1Z**

Optional Accessories		
<u>EWF172</u>	Elkay WaterSentry VII Filter Kit (Coolers + Fountains) <u>Spec Sheet (PDF)</u>	
<u>LK1110</u>	Elkay Glass Filler <u>Spec Sheet (PDF)</u>	
<u>LK1114</u>	Elkay Glass Filler Chrome 2-1/2" x 10" <u>Spec Sheet (PDF)</u>	
<u>97446C</u>	Accessory - Bubbler Kit Vandal-Resistant <u>Spec Sheet (PDF)</u>	O O O

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



Elkay Cooler Wall Mount Non-Filtered Refrigerated 8 GPH Light **Gray Granite** Model EWA8L1Z

These products are designed to operate on 20 psi to 105 psi supply line pressure

tube to attach

٠

1/4" O.D. tube water inlet to

cooler

OPERATION OF QUICK CONNECT FITTINGS

in position

R

Simply push in Tube is secured Push in collet to

cold water supply

release tube

4

Pushing tube in before

pulling it out helps to

С

release tube

3/8" O.D. Tube connect Building water

- 02-07

inlet

Open space rough-in design permits new installation or replacement of existing fountains and coolers with this Elkay cooler when rough-in is within the outline shown.

IMPORTANT! INSTALLER PLEASE NOTE:


This water cooler has been designed and built to provide water to the user which has not been altered by materials in the cooler waterways.

The grounding of electrical equipment such as telephone, computers, etc to water lines is a common procedure. This grounding may be in the building or occur away from the building. This grounding can cause electrical feedback into a water cooler creating an electrolysis which creates a metallic taste or causes an increase in the metal content of the water. This condition is avoidable by installing the cooler using the proper materials as shown below.

NOTICE

The water cooler must be connected to the water supply using a dielectric coupling. The cooler is furnished with a non-metallic strainer which meets this requirement. The drain trap which is provided by the installer should also be plastic to completely isolate the cooler from the building plumbing system.

NOTE: A service supply stop should be installed at the cooler inlet tube.



LEGEND

A = Recommended water supply location 3/8" O.D. unplated copper tube connect stub 1-1/2" (38mm) out from wall shut off by others.
B = Recommended location for waste outlet 1-1/4" O.D. drain.

D = 1-114" Trap not furnished. D = 5/16" (8mm) screw holes in mounting plate. NOTE: New installations must use Ground Fault Circuit Interrupter (GFCI). It is highly recommended that the circuit be dedicated and the load protection be sized for 20 amps.

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.