

**PRODUCT SPECIFICATIONS**

Elkay ezH2O<sup>®</sup> Bottle Filling Station & Versatile Bi-Level ADA Vandal-Resistant Cooler, Non-Filtered Refrigerated Stainless. Chilling Capacity of 8.0 GPH (gallons per hour) of 50° F drinking water, based on 80° F inlet water and 90° F ambient, per ASHRAE 18 testing. Features shall include Antimicrobial, Green Ticker™, Hands Free, Laminar Flow, Real Drain. Furnished with Vandal Resistant bubbler. Electronic Bottle Filler Sensor with Electronic Front and Side Bubbler Pushbar activation. Product shall be Wall Mount (On Wall), for Indoor applications, serving 2 station(s). Unit shall be certified to UL 399 and CAN/CSA C22.2 No. 120. Unit shall be lead-free design which is certified to NSF/ANSI 61 & 372 (lead free) and meets Federal and State low-lead requirements.



|                                 |                                                                                |
|---------------------------------|--------------------------------------------------------------------------------|
| <b>Special Features:</b>        | Antimicrobial, Green Ticker™, Hands Free, Laminar Flow, Real Drain             |
| <b>Finish:</b>                  | Stainless Steel                                                                |
| <b>Power:</b>                   | 115V/60Hz                                                                      |
| <b>Bubbler Style:</b>           | Vandal Resistant                                                               |
| <b>Activation by:</b>           | Electronic Bottle Filler Sensor with Electronic Front and Side Bubbler Pushbar |
| <b>Mounting Type:</b>           | Wall Mount (On Wall)                                                           |
| <b>Chilling Capacity*:</b>      | 8.0 GPH                                                                        |
| <b>Full Load Amps</b>           | 6                                                                              |
| <b>Rated Watts:</b>             | 370                                                                            |
| <b>Dimensions (L x W x H):</b>  | 36-3/4" x 19" x 39-1/16"                                                       |
| <b>Approx. Shipping Weight:</b> | 103 lbs.                                                                       |
| <b>Installation Location:</b>   | Indoor                                                                         |
| <b>No. of Stations Served:</b>  | 2                                                                              |

\*Based on 80° F inlet water & 90° F ambient air temp for 50° F chilled drinking water.

**Special Note: Non-filtered model**

- Green Ticker: Informs user of number of 20 oz. plastic water bottles saved from waste.
- Laminar flow provides clean fill with minimal splash.
- Silver Ion Antimicrobial protection on key plastic components to inhibit the growth of mold and mildew.
- Real Drain System eliminates standing water.

**COOLING SYSTEM**

- Compressor: Hermetically-sealed, reciprocating type, single phase. Sealed-in lifetime lubrication.
- Condenser: Fan cooled, copper tube with aluminum fins. Fan motor is permanently lubricated.
- Cooling Unit: Combination tube-tank type. Continuous copper tubing with is fully insulated with EPS foam that meets UL requirements for self-extinguishing material.
- Refrigerant Control: Refrigerant R-134a is controlled by

**Included with Product:** Water Cooler (EZSTL8WSVRSC), Bottle Filler (EZWSR)

**Ships in multiple boxes.**

AMERICAN PRIDE. A LIFETIME TRADITION. Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and operated company, providing thousands of jobs that support our families and communities.



**PRODUCT COMPLIANCE**

- ADA & ICC A117.1
- ASME A112.19.3/CSA B45.4
- Buy American Act
- CAN/CSA C22.2 No. 120
- GreenSpec<sup>®</sup>
- NSF/ANSI 61 & 372 (lead free)
- UL 399



Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.




**5 Year Limited Warranty** on the refrigeration system of the unit. Electrical components and water system are warranted for 12 months from date of installation. **Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.**

PART: \_\_\_\_\_ QTY: \_\_\_\_\_  
 PROJECT: \_\_\_\_\_  
 CONTACT: \_\_\_\_\_  
 DATE: \_\_\_\_\_  
 NOTES: \_\_\_\_\_  
 APPROVAL: \_\_\_\_\_

*In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.*

accurately calibrated capillary tube.

- Temperature Control: Easily accessible enclosed adjustable thermostat is factory preset. Requires no adjustment other than for altitude requirements.

| Optional Accessories     |                                                                                                              |                                                                                     |
|--------------------------|--------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <a href="#">EWF3000</a>  | Elkay WaterSentry Plus Filter System Kit (Bottle Fillers)<br><a href="#">Spec Sheet (PDF)</a>                |  |
| <a href="#">LKAPREZL</a> | Elkay Cane Apron for EZ Gray<br><a href="#">Spec Sheet (PDF)</a>                                             |  |
| <a href="#">MLP200</a>   | In-wall Carrier for Bi-level On-wall Bottle Fillers, Coolers & Fountains<br><a href="#">Spec Sheet (PDF)</a> |  |

*In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit [elkay.com](http://elkay.com) for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.*