



SURFACE MOUNTED ELECTRONIC BOTTLE FILLER MWSMEBF, MWSM8EBF, MWSM12EBF

Suggested Specification

Model MWSM8EBF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water. Model MWSM12EBF shall deliver 12.0 gph of 50°F water at 90°F ambient and 80°F inlet water. Model MWSMEBF is a non-refrigerated Bottle Filler and delivers ambient water. Water flow to the bottle filler is by means of an sensor activated solenoid. This unit shall include built in bottle counter, flow monitor, filter monitor and filtration for taste odor and chlorine reduction, Key bottle filler components contain Freshield which utilizes a silver based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discoloration, odors and degradation. Basin shall be designed to eliminate splashing and standing water. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1 and ADA.

Models

MWSM8EBF delivers 8.0 gallons of chilled drinking water per hour.
MWSM12EBF delivers 12.0 gallons of chilled drinking water per hour.
MWSMEBF is a non-refrigerated bottle filler.

Standard Features

- > Built-in 100 micron strainer stops particles before they enter the waterway
- > Waterways are Lead-free in Materials & Construction
- > Surface Mounted Heavy Duty steel frame
- > Built in Automatic Bottle Counter
- > Filter Monitor
- > Filtration for taste odor and chlorine reduction

Finishes

- > Standard Cabinet Finish: Brushed Stainless Steel

Installation

- > Prior to installing, consult with local, state and federal codes for proper mounting height
- > Shipped with complete instructions and wall mounted frame
- > Removable front panels allow for easy access to filtration



Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Product Certified to NSF/ANSI Standard 61, Annex G (weighted average lead content of <=0.25%) and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953). The Green Filter has been tested to ANSI/NSF standards 42 not by NSF

Models covered by this specification comply with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards.

Note: chiller units sold with these models must be remotely located, as they do not fit into the housing of the unit, or inside the wall cavity of a typical stud wall.




Oasis International Product Certified by NSF to NSF/ANSI Standard 61, G

Model	50° F Drinking Water 90° F Ambient Air Temp*		115 Volts, 60 HZ			Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Compr. HP	Full Load Amps	Rated Watts		
MWSMSBF				.10	7	Yes	39 Lbs.
MWSM8SBF	8.0	8.0	1/4	4.8	550	Yes	83 Lbs.
MWSM12SBF	12.0	12.0	1/3	5.4	620	Yes	83 Lbs.

*Industry Standard Rating Condition 80° F inlet water temperature.


Specifications subject to change without notice

OASIS® MODULAR SPORTS BOTTLE FILLER MODELS MWSM8EBF, MWSM8EBF, MWSM12EBF



NOTES:

1. RECOMMENDED ADULT HEIGHT INSTALLATION SHOWN. ADJUST VERTICAL DIMENSIONS AS REQUIRED TO COMPLY WITH FEDERAL, STATE AND LOCAL CODES.
2. STOP VALVE, TRAP, PIPE CONNECTOR TO WASTE WASTE LINE NOT PROVIDED. SHORT RADIUS TRAP REQUIRED
3. ALL DIMENSIONS ARE IN INCHES. DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS.



THIRD ANGLE PROJECTION

ROUGHING-IN AND DIMENSIONAL DRAWING