



**UNIVERSAL BARRIER-FREE VERSACOOOLER® II WITH ANTIMICROBIAL COPPER TOP AND NOSE ASSEMBLY Energy and Water Conservation Technology PG8ACSLTM-CSTN, PGACSLTM-CSTN**

**Suggested Specification**

Model PG8ACSLTM-CSTN shall deliver 8.0 gph of 50° F degree water at 90° F ambient and 80° F inlet water. Model PGACSLTM-CSTN is a non-refrigerated drinking fountain and delivers ambient water. Shall include an infrared sensor (left unit only) to activate the flow of water and four antimicrobial copper push pads (right unit only). Basin shall be designed to eliminate splashing and standing water. Water saver bubbler reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be stainless steel with antimicrobial copper top and nose assembly. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with ANSI/NSF 61 and NSF/ANSI 372.

**Models**

- PG8ACSLTM-CSTN delivers 8.0 gallons of chilled drinking water per hour with touch free sensor.
- PGACSLTM-CSTN is a non-refrigerated fountain.

**Standard Features**

- Univesal design allows for univiversal installation
- Built-in 100 micron strainer stops particles before they enter the waterway.
- Waterways are Lead-Free in materials & construction
- Flexible bubbler guard
- Stainless steel top and heavy duty galvanized steel frame
- Antimicrobial copper top and nose assembly
- Four antimicrobial copper push pads - right unit only
- High efficiency cooling system
- Refrigerant R-134a
- Infrared sensor activation - left unit only

**Finishes**

- Standard cabinet finish: Stainless steel

**Installation**

- Prior to roughing consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation.

**Options (at additional cost)**

- Glass fillers (factory installed)
- Push handle (029603-004)
- One piece chrome plated brass bubbler (036700-001)
- Apron for upper unit
- VersaFilter

**Limited 5-Year Warranty**

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

**Export Warranty**

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

**Certifications/Compliance**

- Oasis International Electric Water Coolers are listed by Underwriters Laboratories Inc. and comply with both U.S. and Canadian Requirements.
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for “Lead Free” plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.
- This unit complies with ARI standard 1010 Testing, Operating and Rating requirements (electric water coolers only).
- These waters coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed.



Model	50° F Drinking Water 90° F Ambient Air Temp*			Hot'N Cold Model	115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx
	Rated Capacity GHP	Base Rate GHP	Pre-Cooler		Compr. HP	Full Load Amps	Rated Watts			
PG8ACSLTM-CSTN	8.0	8.0	No	No	1/4	4.4	460	Yes	No	84 Lbs
PGACSLTM-CSTN	Fountain Only					0.10	7	No	No	50 Lbs

\* Industry standard rating condition 80° F inlet water temperature

Specifications subject to change without notice

