



We Know Water.

HANDS-FREE VERSAFILLER® RETROFIT KIT

• PWEBF

Suggested Specification

When retrofitted to either the PG8AC or P8AM, the PWEBF bottle filler has independent contactless activation and laminar flow. VersaFiller alcove contains Freshshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Unit shall include filter monitor and bottle counter. VersaFiller cabinet finish is brushed stainless steel.

When retrofitted to either the PG8AC or P8AM the VersaFiller models satisfy ANSI A117.1 and ADA requirements when properly installed. Units also meet guidelines for children's accessibility providing the floor to orifice height is 30 inches and proper clear floor space is provided for frontal approach. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

| | |
|-------------------------------|---|
| Features: | <ul style="list-style-type: none"> Built-in 100 micron strainer stops particles before they enter the waterway Waterways are lead-free in materials & construction Heavy duty galvanized steel frame Contactless activation bottle filler with programmable auto shut off Ample space within the bottle filler cabinet to add filtration, including all OASIS filters Access through the top of the bottle filler for clean and easy replacement of filters with Tilt 'N Tether Built-in filter monitor and bottle counter LED lighted alcove Surface mount frame assembly |
| Filtration: | Utilizes existing filtration if applicable. Option to add filtration to top of bottle filler. |
| Power: | 115 Volts, 60 Hz |
| Activation By: | Contactless Sensor |
| Mounting Type: | Wall Mounted |
| Chilling Option: | Utilizes existing refrigeration system if applicable |
| Full Load Amps: | 0.2 |
| Rated Watts: | 11 |
| Approx. Net Weight: | 11 lbs. |
| Installation Location: | Indoor |

The PWEBF VersaFiller is designed to retrofit existing OASIS PG8AC and P8AM pressure cooler models. Models that this unit will not retro to are the electric eye P8AC and P8AM units. Units with optional glass fillers must have the glass filler disconnected and removed.



Installation

- Prior to rough-in consult with local, state, and federal codes for proper mounting height.
- Shipped with complete instructions and wall mounting brackets.

Finishes

- VersaFiller cabinet finish is brushed stainless steel

Options

- Elkay Adapter Gasket 041533-001
- OASIS Versafilter III Kit 041253-001

Limited 1-Year Warranty

(Continental limits of the United States and Canada)
One year on components parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



Specifications subject to change without notice

OASIS® PWEBF VERSAFILLER RETROFIT KIT

