

PRODUCT SPECIFICATIONS

Elkav Stainless Steel 22" x 19" x 5-1/2" Wall Hung Lavatory Sink Kit. Sink is manufactured from 18 gauge 304 Stainless Steel with a Buffed Satin finish, Rear Center drain placement, and Bottom only pads.

Material:	304 Stainless Steel
Finish:	Buffed Satin
Gauge:	18
Sound Deadening:	Bottom only pads
Number of Bowls:	1
Sink Dimensions:	22" x 19" x 19-1/8"
Bowl 1 Dimensions:	16" x 11-1/2" x 5-1/2"
Drain Size:	1-1/2" (38mm)
Drain Location:	Rear Center



Included with Product: ELV2219 sink,

one LKB721C sensor faucet with AC

plug-in / 4 AA batteries.

one LK723 thermostatic mixing valve

▼ Ships in multiple boxes.

A Century of Tradition and Quality.

For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



Product Compliance: ADA & ICC A117.1

Faucet:

NSF₂

ASME A112.19.3/CSA B45.4 ASME A112.18.1/CSA B125.1

NSF 372 (lead free)


NSF 61





Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards.

Clean and Care Manual (PDF) Installation Instructions (PDF) - 2000000714 Warranty (PDF)



PART:	QTY:
PROJECT:	
CONTACT:	
APPROVAL:	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



G SINK 10-1/2" 10-1/2" (267mm)(267mm)2-5/8" 14-15/16" 2-5/8" 14-15/16" 1/4" (6mm) x 1" (25mm) LONG SLOT (4 PLACES) (67mm) (125mm) (125mm) (67mm) WALL HANGER 3/8" -13/16" (21mm) (10mm) **OUTLINE OF SINK** Ø 3/8" (10mm) -HOLE (4 PLACES) (127mm)1-1/2" (38mm) I.P.S. WASTE 3-15/16" (100mm) Ø 3/16" (5mm) HOLES (3 PLACES) 32-1/6" (814mm) (PROVIDES 31-1/2" (800mm) FINISHED FLOOR (51mm) 2-5/8" TO RIM HEIGHT) 20-1/2" 1/2" (13mm) I.P.S. SUPPLY INLET (2 PLACES) (67mm) (521mm) 14-15/16 (379mm) 8-1/16" 1-1/8" NOTE: ALL FASTENERS 8" (204mm) (28mm) (203mm) SUPPLIED BY OTHERS Ç SINK FINISHED FLOOR FOR ELV2219 SACMC LK724-MANUAL MIXING VALVE STOP VALVES 11-5/8" (295mm) 3/8 (10mm) SUPPLY LINES TEMP **ADJUST** 7-5/16" (NOT SUPPLIED) (186mm) FOR ELV2219 SACTMC COMPRESSION TO SWEAT ADAPTER 3/8" (10mm) X 1/2" (13mm) 3-REQ'D & 1/2" (13mm) SUPPLY TUBE (NOT SUPPLIED) 5/8" LK723 (14mm) THERMOSTATIC 90° ST. EL MIXING VALVE (2 REQ'D) NOT SUPPLIED 5-5/8" STOP VALVES, FITTINGS & 3/8" (10mm) SUPPLY LINES (NOT SUPPLIED) 23-1/2" (143mm) (597mm) TEMP. **ADJUST** mm NOTE USE TEFLON TAPE FOR ALL WATER CONNECTIONS. DO NOT USE PIPE DOPE.

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.