### Outdoor Bi-Level Pedestal Fountain Non-Filtered Non-Refrigerated Model LK4420

### PRODUCT SPECIFICATIONS

Outdoor Bi-Level Pedestal Fountain Non-Filtered Non-Refrigerated. Features shall include Heavy Duty Vandal Resistant, Laminar Flow, 300 Series Stainless, Furnished with Vandal Resistant bubbler, Mechanical Button activation. Product shall be Floor Mount/Freestanding, for Outdoor applications, serving 2 station(s).

Special Features:	Heavy Duty Vandal Resistant, Laminar Flow, 300 Series Stainless	
Finish:	Black (BK), Blue (BLU), Evergreen (EVG), Gray (GRY)	
Power:	No Electrical Required	
Bubbler Style:	Vandal Resistant	
Activation by:	Mechanical Button	
Mounting Type:	Floor Mount/Freestanding	
Chilling Capacity:	Non-refrigerated	
Dimensions (L x W x H):	14" x 31" x 40-5/16"	
Approx. Shipping Weight:	107 lbs.	
Installation Location:	Outdoor	
No. of Stations Served:	2	
**\//ban used in non-temperature controlled environments unit(s) must		

\*\*When used in non-temperature controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.

- Mechanically-Activated unit continues to supply water in event of service disruptions.
- Laminar flow provides clean fill with minimal splash.



#### **Included with Product: Outdoor Fountain** Ships in one box.

A Century of Tradition and Quality. For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



### PRODUCT COMPLIANCE

ADA & ICC A117.1 ASME A112.19.3/CSA B45.4 NSF REG4







Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF) - 1000003683

Warranty pertains to drinking water applications only. Nondrinking water applications are not covered under warranty. Warranty (PDF)

PART:	QTY:
CONTACT:	
DATE:	
NOTES:	
APPROVAL:	

### **Optional Accessories**

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



# Outdoor Bi-Level Pedestal Fountain Non-Filtered Non-Refrigerated Model LK4420

LK4471LHB	Locking Hose Bib  Spec Sheet (PDF)	
97890C	Accessory - Direct Bury Adaptor <u>Spec Sheet (PDF)</u>	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

## Outdoor Bi-Level Pedestal Fountain Non-Filtered Non-Refrigerated Model LK4420

MOUNTING INSTRUCTIONS and PLUMBING CONNECTIONS

Provide solid, well-drained surface to mount pedestal fountain (concrete pad recommended) with adequate support (300lb. load minimum). (6) 3/8 minimum fasteners (not included) should be attached firmly to mounting surfaces in order to secure unit. (Refer to rough-in diagram)


Locate and install plumbing through ground as required. **NOTE:** Unit is not furnished with service valve.

Position pedestal over plumbing and secure base to fasteners. Remove access panels and connect supply and water lines. Turn on water supply and check for leaks. Reassemble access panels to pedestal.

Trap and service not included.


**OPERATING PRESSURES:** Supply water 20 – 105 psi maximum

### **TOP VIEW**



### **BACK VIEW**

### SIDE & FRONT VIEWS



A = 3/8" O.D. Unplated copper tube connect

shut off valve by others
B = Access Panel (8" X 10")

C = Removable bottom cover

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.