

## PRODUCT SPECIFICATIONS

Elkay Pro Filtration™ Bottle Filling Station & Sgl ADA Cooler Refrigerated Black Total PFAS\*\* + Sediment Prefilter. Chilling Capacity of 8.0 GPH (gallons per hour) of 50° F drinking water, based on 80° F inlet water and 90° F ambient, per ASHRAE 18 testing. Features shall include Antimicrobial\*, Filtered, Green Ticker™, Automatic Filter Status Reset, Hands Free, Laminar Flow, Real Drain, Visual Filter Monitor, Energy Savings, Two Stage Filtration, Alcove Light, Pro Filtration System, Top Mount Quick Filter Change, Stainless Steel Alcove, Automatic Filter Flush, Total PFAS + Lead Filter. Furnished with Flexi-Guard® Safety Bubbler. Electronic Bottle Filler Sensor with Electronic Front and Side Bubbler Pushbar activation. Product shall be Wall Mount (On Wall), for Indoor applications, serving 1 station(s). Unit shall be certified to UL 399 and CAN/CSA C22.2 No. 120.



|                                                                                        |                                                                                                                                                                                                                                                                                                                        |
|----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Special Features:</b>                                                               | Antimicrobial, Filtered, Green Ticker™, Automatic Filter Status Reset, Hands Free, Laminar Flow, Real Drain, Visual Filter Monitor, Energy Savings, Two Stage Filtration, Alcove Light, Pro Filtration System, Top Mount Quick Filter Change, Stainless Steel Alcove, Automatic Filter Flush, Total PFAS + Lead Filter |
| <b>Finish:</b>                                                                         | Black Stainless (BK)                                                                                                                                                                                                                                                                                                   |
| <b>Power:</b>                                                                          | 115V/60Hz                                                                                                                                                                                                                                                                                                              |
| <b>Bubbler Style:</b>                                                                  | Flexi-Guard® Safety Bubbler                                                                                                                                                                                                                                                                                            |
| <b>Activation by:</b>                                                                  | Electronic Bottle Filler Sensor with Electronic Front and Side Bubbler Pushbar                                                                                                                                                                                                                                         |
| <b>Mounting Type:</b>                                                                  | Wall Mount (On Wall)                                                                                                                                                                                                                                                                                                   |
| <b>Chilling Capacity*:</b>                                                             | 8.0 GPH                                                                                                                                                                                                                                                                                                                |
| <b>Full Load Amps</b>                                                                  | 5                                                                                                                                                                                                                                                                                                                      |
| <b>Rated Watts:</b>                                                                    | 352                                                                                                                                                                                                                                                                                                                    |
| <b>Dimensions (L x W x H):</b>                                                         | 18-3/8" x 19" x 46-7/8"                                                                                                                                                                                                                                                                                                |
| <b>Approx. Shipping Weight:</b>                                                        | 81 lbs.                                                                                                                                                                                                                                                                                                                |
| <b>Installation Location:</b>                                                          | Indoor                                                                                                                                                                                                                                                                                                                 |
| <b>No. of Stations Served:</b>                                                         | 1                                                                                                                                                                                                                                                                                                                      |
| *Based on 80° F inlet water & 90° F ambient air temp for 50° F chilled drinking water. |                                                                                                                                                                                                                                                                                                                        |

**Special Note:** plumbSMART Gateway and Account required for cloud connection.

### COOLING SYSTEM

- Compressor: Hermetically-sealed, reciprocating type, single phase. Sealed-in lifetime lubrication.
- Condenser: Fan cooled, copper tube with aluminum fins. Fan motor is permanently lubricated.
- Cooling Unit: Combination tube-tank type. Continuous copper tubing with is fully insulated with EPS foam that meets UL requirements for self-extinguishing material.
- Refrigerant Control: Refrigerant R-134a is controlled by accurately calibrated capillary tube.
- Temperature Control: Easily accessible enclosed adjustable thermostat is factory preset. Requires no adjustment other than for altitude

PART: \_\_\_\_\_ QTY: \_\_\_\_\_  
PROJECT: \_\_\_\_\_  
CONTACT: \_\_\_\_\_  
DATE: \_\_\_\_\_  
NOTES: \_\_\_\_\_ APP  
ROVAL: \_\_\_\_\_

### Included with Product:

**Bottle Filler,  
Water Cooler,  
Total PFAS Filter,  
Sediment Filter**

### Ships in one box.

A Century of Tradition and Quality. For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.

### PRODUCT COMPLIANCE

ADA & ICC A117.1  
ASME A112.19.3/CSA B45.4  
CAN/CSA C22.2 No. 120  
FCC & ISED  
NSF/ANSI 42, 53, 61 (Q≤1), 372 (lead free), & 401  
UL 399



This Zurn Elkay product has a certified Environmental Product Declaration (EPD) that complies with an independently verified life cycle assessment (LCA). Visit [Product Declarations and Certifications](#) for more information.



Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

[Installation Instructions \(PDF\) - 2000002951](#)

**5 Year Limited Warranty** on the refrigeration system of the unit. Electrical components and water system are warranted for 12 months from date of installation. **Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.**

[Warranty \(PDF\)](#)

*In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit [elkay.com](#) for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.*





Model LZS8WSBPRO-FLP4-FSR5

Elkay Pro Filtration™ Bottle Filling Station & Sgl ADA Cooler

Refrigerated Black Total PFAS + Sediment Prefilter


TAG

requirements.

| Features                                                                                                                                         |                                                                                                                                                                                                                                               |  |
|--------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| •                                                                                                                                                | Certified Filtration: Certified by IAPMO R&T to NSF/ANSI 42, 53 and 401 to reduce lead, microplastics, cysts, asbestos, turbidity, particulate class 1, chlorine, and taste and odor, and to NSF/ANSI/CAN 372 for lead free compliance        |  |
| •                                                                                                                                                | Top-Access Filter Replacement: Change filters in seconds from the top- minimizing maintenance time and system disruption                                                                                                                      |  |
| •                                                                                                                                                | High Capacity Filtration: Delivers filter life capacity that exceeds industry standards - extending uptime and reducing filter changeouts                                                                                                     |  |
| •                                                                                                                                                | Smart Connected: Remotely track filter status, anticipate maintenance, flush the unit, and monitor bottles saved for sustainability insights                                                                                                  |  |
| •                                                                                                                                                | Automated Filter Startup: Recognizes new filters, automatically resets status lights, and flushes the waterway- reducing installation time and labor                                                                                          |  |
| •                                                                                                                                                | Interactive Display: Blue LCD display shows remaining filter capacity and 20oz bottles saved - helping teams stay ahead of maintenance and avoid unplanned downtime                                                                           |  |
| •                                                                                                                                                | Advanced filtration designed to reduce Total PFAS***, featuring a 4,000-gallon capacity for targeted contaminant reduction. Stage 1 sediment prefilter captures sediment first, helping extend contaminant filter life and maintain flow rate |  |
| *Antimicrobial claims are in reference to components manufactured antimicrobial agents, helping to provide clean, stain- and odor-free surfaces. |                                                                                                                                                                                                                                               |  |
| **Total PFAS as defined by NSF/ANSI 53.                                                                                                          |                                                                                                                                                                                                                                               |  |

| Optional Accessories            |                                                                                    |                                  |
|---------------------------------|------------------------------------------------------------------------------------|----------------------------------|
| <a href="#">FL6</a>             | Elkay Pro Filtration® High-Capacity Lead + Microplastics 6000 gal. Filter          | <a href="#">Spec Sheet (PDF)</a> |
| <a href="#">FLP4</a>            | Elkay Pro Filtration® Total PFAS* + Lead + Microplastics 4000 gal. Filter          | <a href="#">Spec Sheet (PDF)</a> |
| <a href="#">FL10</a>            | Elkay Pro Filtration® Ultra-Capacity Lead + Microplastics 10000 gal. Filter        | <a href="#">Spec Sheet (PDF)</a> |
| <a href="#">FSR5</a>            | Elkay Pro Filtration® Stage 1 Sediment Prefilter                                   | <a href="#">Spec Sheet (PDF)</a> |
| <a href="#">ZGW-LORA-W1-LTE</a> | Zurn Gateway for Connected Enabled Products                                        | <a href="#">Spec Sheet (PDF)</a> |
| <a href="#">SSBFUP-PRO</a>      | Back Panel Assembly Kit for Single Coolers with Elkay Pro Filtration Bottle Filler | <a href="#">Spec Sheet (PDF)</a> |
| <a href="#">MLP100</a>          | In-wall Carrier for Single-station On-wall Bottle Fillers Coolers & Fountains      | <a href="#">Spec Sheet (PDF)</a> |

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit [elkay.com](#) for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit [elkay.com](http://elkay.com) for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.