

WL250 Performance worthy of an encore and functional design for the workplace

0

waterlogic

.

waterlogic

Refreshing water for any working environment

With a choice of hot or cold, the WL250 is a popular choice for offices and factories where great quality water is required.

Advanced technology

The WL250 features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards by IAPMO R&T, carrying the Water Quality Platinum Seal, meaning they offer the best possible filtration. Multi-stage filtration removes common water contaminants and chlorine to dramatically improve water taste and odor.



In-tank UV sanitization

Waterlogic's in-tank UV technology acts against waterborne microorganisms and bacteria, dispensing great quality water, glass after glass.



BioCote®* product protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®* technology, a silver ion additive that inhibits the growth of odor and stain causing microbes, such as bacteria and mold.

Simply great, clear water**

Free from fluoride, free from chlorine, and free from water-borne tastes and odors. (Dependent on filters type and water conditions.) **Filtration results based on the use of RO, GAC, CBC, or sediment filters.

*BioCote[®] silver ion technology protects surfaces from odor- and stain-causing microbes. BioCote[®] does not protect users or others against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

Features

In-tank UV technology is highly effective against germs and bacteria. A UV lamp treats the water stored in the reservoir for fast, reliable, and easy water purification

Removable drip tray to collect accidental spillage

BioCote[®] treated dispensing area to protect it from odor and stain causing microbes

Thermal overload protection

Easy connection to the existing water supply

Leak detection for peace of mind

Water options

cold hot

Number of users: 10-30

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding 13.6" (W) x 40.2" (H) x 14.4" (D) Countertop 13.6" (W) x 17.7" (H) x 14.4" (D)

Dispensing area height

8.5″

Weight Freestanding: 58lbs

Countertop: 42lbs

Recommended filtration

Sediment, GAC, CBC with lead and cyst removal (dependent on local water conditions)

Storage capacity

Hot tank 1.6 liters Cold tank (freestanding): 4 liters Cold tank (countertop): 2 liters

Drip tray capacity

.4 US gal

Compressor

120V/60Hz

Water temperatures settings

Cold: 37-54°F (default) Hot: 187°F

Contact us today

Blueline 630 Allendale Road, Suite 200 King of Prussia, PA 19406

Sales: (866) 289-7518 Support: (855) 434-5337 orders@blueline.com https://bluline.com/contact-us/

Tested and certified







Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.