



MODEL 8880 Fountain



This fountain is certified to NSF/ANSI 61.

GENERAL

Fully recessed fountain, non-corrosive stainless steel number 300 series with brushed satin finish. One-piece, contour-formed basin with rounded corners and edges reduces splatter, insures proper drainage and prevents standing waste water. Ideally suited for installation in high traffic areas. When properly installed, unit meets state and federal requirements as defined by the Americans with Disabilities Act for side approach.

BUBBLER

Exclusive one-piece, chrome-plated two-stream mound-building bubbler with non-removable anti-squirt feature and integral hood insures a satisfying drink of water.

PUSHBUTTON ACTUATION MECHANISM

Self closing, vandal-resistant pushbutton does not require grasping or twisting.

AUTOMATIC STREAM HEIGHT REGULATOR

Self-closing assembly is located inside unit to prevent tampering. Unit resists corrosion and liming. A constant stream height is automatically maintained under line pressures that vary from 20 to 105 psi.

INLET STRAINER

Easily cleaned in-line strainer screen traps particles of 140 microns or larger before they enter the waterway.

WATER INLET

3/8" O.D. Tubing

DRAIN OUTLET

1-1/2" tube outlet for 1-1/2" slip joint connection.

SUGGESTED SPECIFICATIONS

Fountain shall include pushbutton on the front, contour-formed basin to eliminate splashing and standing water, and shall have rounded corners and edges. Projector shall be two-stream, mound-building type with integral hood guard and anti-squirt feature. Cooler shall comply with ANSI 117:1 and **ADA for side approach only**. The manufacturer shall certify the unit to meet the requirements of NSF/ANSI 61, and the Safe Drinking Water Act.

Note: Continued product improvement makes specifications subject to change without notice. See Halsey Taylor website for most current spec sheet.

Fully Recessed Fountain



Standard finish is Stainless Steel

Optional Accessories (extra cost)

- Glass Filler (factory installed - No. 2408 style glass filler only).
- Vandal-Resistant Kit
- Easy-Flex™ Bubbler

Each 8880 consists of 2 cartons of the following:

Fountain & Miscellaneous Parts
Mounting Frame

Trap and service stop not included.

Shipping weight: 33 lbs.

JOB NAME: _____ _____ _____
ENGINEER/CONTRACTOR NAME: _____
APPROVAL: _____
DATE: _____



* For parallel approach only

