

FEATURES & BENEFITS

AUDIBLE/VISUAL ALARM

Notification of an emergency is clearly noticeable with a brightly flashing amber light and easily recognizable with a 90 db buzzer.

FLOW SWITCH

The alarm is activated by an included Model SP154DPDT 1-1/4" NPT double pole, double throw stainless steel and powder coated aluminum flow switch that is supplied with an extra set of electrical contacts for remote alarm hook-up.

ELECTRICAL

110/120 VAC, 50 or 60 Hz; 0.12A average current draw during operation.

MOUNTING

Recessed alarm can be mounted in-wall with a recessed electrical box. Required components (not included): 1/2" flex conduit, mounting hardware, and wiring materials.



OPTIONS

For more information, visit www.hawsc.com or call (888) 640-4297.

SPECIFICATIONS

Model 9001R recessed emergency alarm and light system features an amber flashing light and 90 db at 10 feet (304.8 cm), buzzer that is operated by a double pole, double throw flow switch. Unit is activated when the emergency shower or eyewash is in operation. System can be mounted in-wall. Unit is recommended to be installed where an emergency shower or eyewash is installed in a remote or noisy location where user is unable to summon help.

- Brightly flashing amber light and 90 db buzzer brings immediate attention to an emergency situation
- Switch will activate at 3 gpm (11.4 L)
- Voltage: 110/120 VAC, 50 or 60 Hz
- Flow Switch: 1-1/4" NPT inlet and outlet.
- This alarm contains a multiple set of contacts for remote activation alarm sites
- Individual components are UL listed
- Indoor applications only

Product Includes:

- Recessed amber alarm light with 90db audible buzzer
- [1-1/4" Flow Switch | Model: SP154DPDT](#)
- Electrical Box w/ Extension Ring

APPLICATIONS

Specifically, this alarm can be used with almost any Haws combination shower/eyewash model.



