

GS Series

MODEL GSM55

BARRIER FREE, BI-LEVEL,
PEDESTAL MOUNTED
DRINKING FOUNTAIN

STANDARD FEATURES

- Resistant to sunlight, heat, moisture and wear
- 18 gage, 304 stainless steel bowl
- 12 gage, heavy duty stainless steel, corrosion and scratch resistant finish
- Polished stainless steel, anti-rotation non-squirt bubbler
- 100 mesh inlet strainer
- Access door, heavy duty steel, vandal resistant
- Vandal resistant stainless steel bottom plate

SUGGESTED SPECIFICATIONS

Model GSM55 is a barrier free pedestal mounted, vandal resistant, bi-level square drinking fountain made from 18 gage, 304 stainless steel bowls mounted into a green powder coated 12 gage, heavy duty stainless steel pedestal. Unit shall be activated by front mounted self-closing buttons, by using less than 5 pounds of force, which activates internally mounted valves with adjustable stream regulators controlling the water flow. Bubblers shall be polished stainless steel with non-squirt features and operate on water pressure range of 20-105 psig. Fountain is certified to ANSI A117.1, Public Law 111-380 (NO-LEAD), CHSC 116875 and NSF/ANSI 61, Section 9. Fixture meets ADA, ADA Standing Person, and ADA Child requirements when mounted appropriately.

Options Notes:

¹ See separate option sheet.

² This option is not available freeze-resistant.



MODEL:

(Must Specify)

- | | |
|--------------------------------|-----------------------------|
| ☐ GSM54 | Satin stainless finish |
| ☐ GSM55 | Green powder-coated (Shown) |
| ☐ GSM56 | Red powder-coated |
| ☐ GSM57 | Blue powder-coated |

Custom color finishes available upon request

OPTIONS

(additional costs may be incurred)

- | | |
|--------------------------------|---|
| ☐ -CH30 | Child height, 30" bubbler height |
| ☐ -FRU2 | Freeze resistant, 2 valves ¹ |
| ☐ -FRU3 | Freeze resistant, 3 valves ¹ |
| ☐ -FRU4 | Freeze resistant, 4 valves ¹ |
| ☐ -FS | Foot spray |
| ☐ -HB1 | Hose bibb, compression, with hose threaded outlet/VB ^{1 2} |
| ☐ -HB2 | Hose bibb, loose key, with hose threaded outlet/VB ^{1 2} |
| ☐ -HB3 | Hose bibb, loose key, vandal resistant, with hose threaded outlet/VB ^{1 2} |
| ☐ -IGM | In-ground 14" mounting |
| ☐ -JF1 | Jug filler, spigot, self-closing valve with plain end ^{1 2} |
| ☐ -JF2 | Jug filler, pushbutton, self-closing valve with plain end ¹ |
| ☐ -NP2 | Non-pollutable, freeze resistant, 2 valves |
| ☐ -NP3 | Non-pollutable, freeze resistant, 3 valves |
| ☐ -NP4 | Non-pollutable, freeze resistant, 4 valves |
| ☐ -PF | Pet fountain receptor ¹ |

Complies with the following standards:



Member of
U.S. Green
Building
Council



Recyclable
Product



Water
Conserving
Product

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA
Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com


Member of
MORRIS GROUP
INTERNATIONAL

IMPORTANT: INSTALLATION AND SITE PREP FOR FREEZE RESISTANT OPTIONS "-FRU, -NP" WILL DIFFER FROM STANDARD. REFER TO DESIGNATED FREEZE RESISTANT INSTALLATION DETAILS.

GS Series

MODEL GSM55

BARRIER FREE, BI-LEVEL
PEDESTAL MOUNTED
DRINKING FOUNTAIN



* Valve specifications:
Minimum/Maximum Pressure
30 to 100 psi.

GENERAL NOTES:

1. ALL DIMENSIONS ARE IN INCHES [MM].
- *2. STANDARD ADULT HEIGHT MODEL SHOWN. OPTIONAL -CH30 CHILD HEIGHT MODEL AVAILABLE.
3. STOP VALVE NOT PROVIDED.

Murdock Mfg.™ warrants that its products are free from defects in material or workmanship under normal use and service for a period of one year from date of shipment. Murdock's liability under this warranty shall be discharged solely by replacement or repair of defective material, provided Murdock™ is notified in writing within one year from date of shipment, F.O.B. Industry, California.

SELECTION SUMMARY & APPROVAL FOR MANUFACTURING

Model Number & Options _____ Quantity _____

Company _____

Contact _____ Title _____

Signature _____ Date _____
(Approval for Manufacturing)

All dimensions are subject to manufactures tolerance of plus or minus 1/2" nominal and subject to change without notice. Murdock assumes no responsibility for use of void or superseded data. Dimensions may change with the addition of optional accessories. Murdock Mfg.™, Member of Morris Group International™. Please visit www.murdockmfg.com for most current specifications.