



## DropSpot™ Bottle Fillers & Water Coolers

### DRS120-UNFIL-UNREF-SS

#### Product description

Unfiltered, Unrefrigerated, 304 Stainless Steel, DropSpot™ On-wall Bottle Filler with Bi-level Cooler.

#### Compliances & Certifications



(ASME A112.18.1 Compliant, UL Certified (US and Canada), cUPC Certified, FCC Compliant, IAPMO, IAPMO listed ASME, IGC 115, IGC 226, MA Approved, Meets Canada OBC and QBC, NSF-61/CAN-61, NSF-372 Lead Free, AB100, NSF/ANSI/CAN 61: Q ≤ 1.0, TAS, UL 399/CSA C22.2 No.120)

#### Code 33820065

#### Finish

- 304 Stainless Steel (SS)

#### Downloads

- [DRS120\\_DRS125 Refrigerated Bi-level Cooler Installation Instructions.pdf](#)
- [DRS120\\_DRS125 Unrefrigerated Bi-level Cooler Installation Instructions.pdf](#)
- [FA3000 DRS110\\_115\\_120\\_125 Drop Down Filter Assembly Installation Instructions.pdf](#)
- [FC3000 Replacement Water Filter Cartridge Installation Instructions.pdf](#)
- [Sloan DropSpot Bottle Fillers and Water Coolers Brochure.pdf](#)
- [DropSpot™ Care and Cleaning Guide.pdf](#)
- [Additional Downloads](#)

#### Videos

- [Sloan DropSpot™ Bottle Fillers and Water Coolers](#)
- [Sloan DropSpot™ Bottle Fillers and Water Coolers Now at Wrigley Field](#)

## Details

- Mounting: On-wall
- Configuration: Bottle Filler with Bi-level Cooler
- Filter Option: Unfiltered (UNFIL)
- Refrigeration Option: Unrefrigerated (UNREF)
- Finish: 304 Stainless Steel (SS)
- Full Load Amps: 5.3
- Installation Location: Indoor
- Bottle Filler Water Flow Rate: Up to 1.2 gpm (4.5 Lpm)
- Bubbler Flow Rate: 0.3 gpm (1.1 Lpm)

## Features

Sloan Bi-Level Bottle Filler Drinking Fountain Combo available in both Stainless and Black, filtered and unfiltered, refrigerated and unrefrigerated options.

- Touch-free sensor operated bottle filler with 20 second max run time, Up to 1.2 gpm fill rate for quick fill with laminar flow
- Versatile mounting style allows for left-high or right-high installation, ADA compliant when installed properly
- Backlit LED light that illuminates bottle filling area when sensor is activated, Soft ambient white light to indicate filter status
- Bottle Counter Display indicates the number of 16 oz plastic bottles saved as well as the ounces of water dispensed for water consumption tracking
- Rough-in matches other manufacturers' recommended rough-in locations for easy replacement
- Antimicrobial bubbler, push bar, and other components
- Drop-down door assembly provides easy access to filter
- Patent pending push bar activates at any touch point and provides easy access for cartridge replacement
- Optional cane apron available for bi-level units to assist with ADA compliance (part 33830030, 33830031). Sold separately
- All models IoT compatible with subscription to SC Argus® Pro SaaS

## Recommended specifications

Sloan's DropSpot™ On-wall Bottle Filler with Bi-level Cooler UnFiltered Unrefrigerated Stainless. Unit shall be activated from an antimicrobial front pushbar using less than 5 pounds of force. Bubbler shall deliver a 0.3 gpm flow. Basin and cabinet shall be constructed from 304 stainless steel with satin finish. Bottle filler shall include sensor operated activation with a 20 second maximum run time. Bottle counter display indicates the number of 16 oz plastic bottles saved as well as the ounces of water dispensed for water consumption tracking. White light indicates the water filter status. Unit shall include LED lights that illuminate the bottle filling area. Bottle filler housing construction shall be stainless steel. Bottle filler shall provide up to 1.2 gpm flow rate with a laminar flow. Push bar shall be activated by any touch point on the bar and shall be opened by Sloan access key.

## Power

- (Standard) 115VAC
- 60Hz
- 5.3A
- Provide Receptacle on GFCI Protected Circuit

## Warranty

[View Warranty Information](#)

## Notes

All information contained within this document subject to change without notice.

Prior to roughing in, consult local, state, and federal codes for proper mounting height.

