



DropSpot™ Bottle Filler & Water Cooler

DRS125-FIL-REF-BLK

Product description

Filtered, Refrigerated, Black, DropSpot™ On-wall Bi-level Cooler.

Compliances & Certifications



(ASME A112.18.1 Compliant, UL Certified (US and Canada), cUPC Certified, FCC Compliant, Michigan Filter First, IAPMO, IAPMO Water, IAPMO listed ASME, IGC 115, IGC 226, Meets Canada OBC and QBC, Filter listed to (NSF-42, NSF-53, NSF-401), NSF-61/CAN-61, NSF-372 Lead Free, NSF-401, AB100, NSF/ANSI/CAN 61: Q ≤ 1.0, TAS, UL 399/CSA C22.2 No.120)

Code 33820084

Finish

 Black (BLK)

Downloads

- [↗ DRS120_DRS125 Refrigerated Bi-level Cooler Installation Instructions.pdf](#)
- [↗ DRS120_DRS125 Unrefrigerated Bi-level Cooler Installation Instructions.pdf](#)
- [↗ FA3000 DRS110_115_120_125 Drop Down Filter Assembly Installation Instructions.pdf](#)
- [↗ FC3000 Replacement Water Filter Cartridge Installation Instructions.pdf](#)
- [↗ Sloan DropSpot Bottle Fillers and Water Coolers Brochure.pdf](#)
- [↗ DropSpot™ Care and Cleaning Guide.pdf](#)
- [↗ Additional Downloads](#)

Videos

- [▶ Sloan DropSpot™ Bottle Fillers and Water Coolers](#)
- [▶ Sloan DropSpot™ Bottle Fillers and Water Coolers Now at Wrigley Field](#)

Details

- Mounting: On-wall
- Configuration: Bi-level Cooler
- Filter Option: Filtered (FIL)
- Refrigeration Option: Refrigerated (REF)
- Finish: Black (BLK)
- Chilling Capacity: 8.0 gph (30.3 Lph)
- Full Load Amps: 5.3
- Installation Location: Indoor
- Bubbler Flow Rate: 0.3 gpm (1.1 Lpm)

Features

Sloan Bi-Level Cooler is available in both Stainless and Black, filtered and unfiltered, refrigerated and unrefrigerated options.

- Antimicrobial bubbler, push bar, and other components
- ADA compliant when installed properly
- Rough-in matches other manufacturers' recommended rough-in locations for easy replacement
- Drop-down door assembly provides easy access to filter
- Patent pending push bar designed to be activated at any touch point and to provide easy access for cartridge replacement
- Effectively reduces Total PFAS, lead, microplastics, cysts, Particulates Class 1, and chlorine

Recommended specifications

Sloan's DropSpot™ On-wall Bi-level Cooler Filtered Refrigerated Black. Chilling capacity of 8.0 gph of 50F drinking water, based on 80F inlet water and 90F ambient. Unit shall be activated from an antimicrobial front pushbar using less than 5 pounds of force. Bubbler shall deliver a 0.3 gpm flow. Basin and cabinet shall be constructed from 304 stainless steel with satin finish. Push bar shall be activated by any touch point on the bar and shall be opened by Sloan access key. Filter drop-down assembly shall be opened by Sloan access key. Filter used in the unit shall have capacity of 3000 gallons at a minimum, and shall reduce Total PFAS, lead, microplastics, cysts, Particulates Class 1, and chlorine.

Power

- (Standard) 115VAC
- 60Hz
- 5.3A
- Provide Receptacle on GFCI Protected Circuit

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Prior to roughing in, consult local, state, and federal codes for proper mounting height.

