



OASIS INTERNATIONAL



FREE-STANDING LARGE CAPACITY
CORROSION PROOF

PLF20FACP

Suggested Specification

Cabinet finish shall be Stainless Steel. Internal components shall be corrosion protected. High efficiency Cooling system shall use R-134a refrigerant. Shall be listed by Underwriter's Laboratories to U.S. and Canadian standards and conform to European Union Directives.

Models

PLF20FACP delivers 20 gph of chilled drinking water is corrosion resistant and has a stainless steel cabinet, frame, and fasteners. Special protective coating is applied to compressor, condenser, cooling tank, pre-cooler, water drain and interconnecting water and refrigerant lines.

Standard Features

- > Waterways are lead-free in materials and construction
- > Dial-A-Drink® Bubbler
- > Stainless steel top
- > Stainless steel cabinet with separate galvanized steel base
- > High-efficiency cooling tank and coil.
- > Refrigerant R-134a
- > Limited 5-year warranty

Finishes

- > Standard cabinet finish: Stainless Steel

Installation

- > Prior to roughing-in, consult local, state and federal codes
- > Shipped with complete instructions



Options

- Push Handle 029603-004
- Push Back 029603-005
- Push Down 029603-006
- Kit 031505-001 is required for Field Installation of the above glass fillers
- Foot pedal operated

Limited 5-Year Warranty (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Export Warranty: One year on sealed refrigeration system and most parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Models covered by this specification comply with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards and European Union Directives.

Components in this cooler are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.



Model	Capacities*				115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Options	Net Wt. Approx.
	Cooling Capacity GPH (LPH)	Base Rate GPH (LPH)	Pre-Cooler	Hot 'N Cold™ Model	Compr. HP	Full Load Amps	Rated Watts			
PLF20FACP	20.0	11.0	Yes	No	1/3	7.3	600	Yes	No	91 Lbs.

* Industry Standard Rating Condition 80°F inlet water temperature..

Specifications subject to change without notice

