The G3 has adjustable cooling capabilities and guarantees quality, reliability, and ease of service. The G3's sleek and stylish design is sure to fit in any home or office setting.

Filter System

Standard Filter G3F Stage 1:5 micron Sediment Stage 2:1 micron Activated Carbon Stage 3: 0.5 micron Post Carbon Reverse Osmosis Filter G3RO Above 3 stages plus Stage 4: 50-GPD RO Membrane

Specifications

Dimension: 13"W x 15"D x 42"H Shipping Weight: 58 lb Cold tank volume: 1 gal Hot tank volume: .5 gal Cooling Rate 1.5 gal/hr 37-50 °f Heating Rate 1.3 gal/hr 180 °f



Features

Large dispensing gap ideal for filling large bottles LED lights let you know water has reached the ideal temperature Filter assembly is easily accessible Stainless steel hot and cold tanks

Model G3 **Global Water**



PURE, ENDLESS WATER



866-289-7518

3 Stage Filtration or 4 stage Reverse Osmosis Filtration Technology

Stage 1

5 Micron Sediment Filter

The first stage is a 5 micron Sediment filter that helps improve Sediment such as sand, rust and silt that is present in most municipal water sources.

Stage 2

1 Micron Granulated Activated Carbon Filter

The second stage of filtration is a 2 micron, granulated activated Carbon filter. This filter uses an advanced Carbon technology to remove hundreds of cancer-causing constituents such as pesticides, insecticides, petrochemicals, M.T.B.E's, PCB's, defoliants, and benzene.

Stage 3

Reverse Osmosis Technology

The 3rd stage utilizes Reverse Osmosis technology, which removes any molecular compounds smaller in size than water molecules. Such compounds include salt, manganese, iron, fluoride, lead, and calcium.

Stage 4

0.5 Micron Carbon Block Filter

The 4th and final stage is a 0.5 micron Carbon block filter, which gives the water a final "polish". It removes 99% of lead and microbial cysts such as giardia and cryptosporidium. It also ensures that all chlorine has been removed, and that the water entering the holding tanks is completely odorless.

Available options:

Add Nano Silver Carbon Filter. Upgrade to 180GPD Membrane.





Filter life 2500 Gallons or every 6 months Replace (RO) Membrane every 3-4 years

