



**We Know Water.**

## MODULAR RADII™ FOUNTAIN WITH BUILT IN CONTACTLESS BOTTLE FILLER

- **M8WREBF**
- **M12WREBF**
- **MWREBF**

### Suggested Specification

Model M8WREBF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model M12WREBF shall deliver 12.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model MWREBF is a non-refrigerated unit and shall deliver ambient water. Shall be recessed in design. Shall include the Aqua Pointe™ Bottle Filler with contactless activation and laminar flow. Bottle Filler alcove and cabinet finished shall be stainless steel. Shall include two vandal-resistant push buttons to activate the flow of water and a low flow one piece bubbler with flexible guard. The fountains shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Key Aqua Pointe™ bottle filler components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



	M8WREBF	M12WREBF	MWREBF
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Built-in 100 micron strainer stops particles before they enter the waterway</li> <li>• Waterways are Lead-Free in materials &amp; construction</li> <li>• High efficiency cooling system</li> <li>• Heavy duty galvanized steel frame</li> <li>• Contactless activation bottle filler with programmable auto shut off</li> <li>• Vandal-resistant push button</li> <li>• Flexible bubbler guard</li> <li>• Built-in filter monitor and bottle counter</li> <li>• Logos permanently formed into the alcove and stainless steel wrapper</li> <li>• LED lighted alcove</li> <li>• Built in panel locks for easy access to chiller and filtration if applicable</li> </ul>		
<b>Filtration:</b>	Option to add filtration		
<b>Power:</b>	115 Volts, 60 Hz		
<b>Activation By:</b>	Contactless Sensor on Bottle Filler and Manual Activation on Fountain.		
<b>Mounting Type:</b>	In Wall		
<b>Chilling Option:</b>	8.0 gph*	12.0 gph*	Non-Refrigerated
<b>Full Load Amps:</b>	5.0 amps	5.5 amp	0.2 amps
<b>Rated Watts:</b>	500	550	11
<b>Approx. Net Weight:</b>	102 lbs	106 lbs	50 lbs
<b>Installation Location:</b>	Indoor		

### Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions
- Recessed mounting frame included

### Finishes

- Standard cabinet finish: Stainless steel

### Options

- One piece chrome plated brass bubbler (036700-001)
- OASIS Versafilter III Kit 041253-001

### Limited 5-Year Warranty

(Continental limits of the United States and Canada)  
Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

### Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

### Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Specifications subject to change without notice

# OASIS® MODULAR RADII™ FOUNTAIN WITH BUILT IN CONTACTLESS BOTTLE FILLER

