



**We Know Water.**

**SURFACE MOUNT MODULAR CONTACTLESS QUASAR® VERSAFILLER**

- **MWSMEBQ**
- **MWSM8EBQ**
- **MWSM12EBQ**

**Suggested Specification**

Model MWSM8EBQ shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model MWSM12EBQ shall deliver 12.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model MWSMEBQ is a non-refrigerated unit. Shall be surface mount in design. Water flow to the bottler filler is by means of an electronically activated solenoid.

QUASAR bottle filler shall have UV-C LED treatment at the dispense point, which disinfects the water while it is being dispensed. UV-C LED also cycles on periodically to keep the dispense point sanitized between dispenses.

Shall include the Aqua Pointe™ Bottle Filler with contactless activation and laminar flow. Bottle Filler alcove and cabinet finish shall be stainless steel. Key Aqua Pointe™ bottle filler components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



**Installation**

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions
- Surface mount frame included, but water supply and drain required

**Finishes**

- Standard cabinet finish: Stainless steel

**Options**

- OASIS VersaFilter III Kit 041253-001
- Remedi Filter

**Limited 5-Year Warranty**

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

**Export Warranty**

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

**Certifications/Compliance**

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These waters coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

	MWSM8EBQ	MWSM12EBQ	MWSMEBQ
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Contactless QUASAR with mercury-free UV-C LED treatment at the dispense point</li> <li>• Built-in 100 micron strainer stops particles before they enter the waterway</li> <li>• Waterways are Lead-Free in materials &amp; construction</li> <li>• High efficiency cooling system</li> <li>• Heavy duty galvanized steel frame</li> <li>• Contactless activation bottle filler with programmable auto shut off</li> <li>• Built-in filter monitor and bottle counter</li> <li>• Logos permanently formed into the alcove and stainless steel wrapper</li> <li>• LED lighted alcove</li> <li>• Built in panel locks for easy access to chiller and filtration</li> </ul>		
<b>Filtration:</b>	Option to add filtration		
<b>Power:</b>	115 Volts, 60 Hz		
<b>Activation By:</b>	Contactless Sensor		
<b>Mounting Type:</b>	Wall Mount		
<b>Chilling Option:</b>	8.0 gph*	12.0 gph*	Non-Refrigerated
<b>Full Load Amps:</b>	5.0 amps	5.4 amps	0.40 amps
<b>Rated Watts:</b>	500	540	25
<b>Approx. Net Weight:</b>	97 lbs	101 lbs	48 lbs
<b>Installation Location:</b>	Indoor		

**WARNING:**



Cancer and Reproductive Harm  
www.P65Warnings.ca.gov



\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Specifications subject to change without notice

