



**We Know Water.**

**FREE STANDING CONTACTLESS QUASAR® BOTTLE FILLER**

- **PCPI0EBQ**
- **PCPEBQ**

**Suggested Specification**

Model PCPI0EBQ shall deliver 10.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PCPEBQ is a non-refrigerated bottle filler and delivers ambient water. Shall be freestanding in design with contactless activation for the dispensing of water and laminar flow. Bottle Filler alcove and cabinet finish shall be stainless steel.

QUASAR bottle filler shall have UV-C LED treatment at the dispense point, which disinfects the water while it is being dispensed. UV-C LED also cycles on periodically to keep the dispense point sanitized between dispenses.

Plastic bottle filler components contain Freshield, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Evaporator shall be high efficiency tank type and shall be encapsulated in insulation. An adjustable thermostat having an off position shall control refrigeration system. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



UV-C LED Treatment at the point-of dispense

	PCPI0EBQ	PCPEBQ
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Contactless QUASAR bottle filler with mercury-free UV-C LED at the dispense point</li> <li>• Built-in 100 micron strainer stops particles before they enter the waterway</li> <li>• Waterways are lead-free in materials &amp; construction</li> <li>• Contactless activation bottle filler with programmable auto shut off</li> <li>• High efficiency cooling system</li> <li>• High flow output of 1.1 gallons per minute for faster fill up</li> <li>• Built in drain - no drip tray to empty</li> <li>• Removable front panel for ease of filter change-out (not included)</li> <li>• Built-in filter monitor and bottle counter</li> <li>• Logos permanently formed into the alcove and stainless steel wrapper</li> <li>• LED lighted alcove</li> </ul>	
<b>Filtration:</b>	Option to add filtration	
<b>Power:</b>	115 Volts, 60 Hz	
<b>Activation By:</b>	Contactless Sensor on Bottle Filler	
<b>Mounting Type:</b>	Free Standing	
<b>Chilling Option:</b>	10.0 gph*	Non-refrigerated
<b>Full Load Amps:</b>	5.0 amps	0.4 amps
<b>Rated Watts:</b>	500	25
<b>Approx. Net Weight:</b>	68 lbs	45 lbs
<b>Installation Location:</b>	Indoor	

\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

**Finishes**

- Standard cabinet finish: Brushed stainless steel

**Options**

- OASIS VersaFilter III Kit 041253-001
- Remedi Filter

**Limited 5-Year Warranty**

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

**Export Warranty**

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

**Certifications/Compliance**


- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Specifications subject to change without notice


# OASIS™ FREE STANDING CONTACTLESS BOTTLE FILLER WITH QUASAR




PLAN VIEW

ALL DIMENSION ARE IN INCHES.  
DIMENSIONS IN BRACKETS [ ] ARE IN MILLIMETERS.


ALLOW 4"[102] FOR VENTILATION AT THE REAR OF THE WATER COOLER AND THE SIDES IF SET IN AN ALCOVE OR NEAR A CORNER.



FRONT VIEW



RIGHT SIDE



REAR VIEW