



# We Know Water.

## CONTACTLESS VERSACOOLER® II WITH CONTACTLESS QUASAR™ VERSAFILLER®

- **PG8EBQT**
- **PGEBQT**

### Suggested Specification

Model PG8EBQT shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. PGEBQT is a non-refrigerated model and delivers ambient drinking water. Shall include the VersaFiller® with contactless activation and laminar flow; lower unit shall have infrared sensor to activate the flow of water for the cooler Bottle Filler alcove and cabinet finish shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI.

QUASAR bottle filler shall have UV-C LED treatment at the dispense point, which disinfects the water while it is being dispensed. UV-C LED also cycles on periodically to keep the dispense point sanitized between dispenses.

Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



	PG8EBQT	PGEBQT
<b>Features:</b>	•	Contactless QUASAR with mercury-free UV-C LED treatment at the dispense point
	•	Built-in 100 micron strainer stops particles before they enter the waterway
	•	Waterways are Lead-Free in materials & construction
	•	High efficiency cooling system
	•	Stainless steel top and heavy duty galvanized steel frame
	•	Contactless activation bottle filler with programmable auto shut off
	•	Ample space within the bottle filler cabinet to add filtration, including all OASIS filters
	•	Flexible one-piece water saver bubbler infused with silver-based antimicrobial additive
	•	Includes integral self-scouring waste drain
	•	External access to stream height adjustment on lower VersaCooler fountain
	•	External access to thermostat with tool activated OFF position
	•	Built-in filter monitor and bottle counter
	•	Logos permanently formed into the alcove and stainless steel wrapper
	•	LED lighted alcove

<b>Filtration:</b>	Option to add filtration	
<b>Power:</b>	115 Volts, 60 Hz	
<b>Activation By:</b>	Contactless Sensor on Bottle Filler and Fountain	
<b>Mounting Type:</b>	Wall Mounted	
<b>Chilling Option:</b>	8.0 gph*	Non-Refrigerated
<b>Full Load Amps:</b>	5.0 amps	0.4 amps
<b>Rated Watts:</b>	500	20
<b>Approx. Net Weight:</b>	64 lbs	33 lbs
<b>Installation Location:</b>	Indoor	

\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

### Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

### Finishes

- Standard cabinet finish: Greystone powder coated paint on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

### Options

- One piece chrome plated brass bubbler (036700-001)
- OASIS Versafilter III Kit 041253-001
- Remedi Filter

### Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

### Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

### Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



Specifications subject to change without notice

# OASIS CONTACTLESS VERSACOOLER® II WITH QUASAR™ VERSAFILLER®

