



We Know Water.

CONTACTLESS BI-LEVEL VERSACOOLER® II WITH CONTACTLESS VERSAFILLER® WITH VERSAFILTER™ III

- **PG8FEBFSLTT**
- **PGFEBFSLTT**

Suggested Specification

Model PG8FEBFSLTT shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGFEBFSLTT is a non-refrigerated model and delivers ambient drinking water. Shall include the VersaFiller Sports Bottle Filler with contactless activation and laminar flow; fountains shall have independent activation using contactless infrared sensor to activate the flow of water. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards, and comply with NSF/ANSI 61 and NSF/ANSI 372.



| | PG8FEBFSLTT | PGFEBFSLTT |
|-------------------------------|---|-------------------|
| Features: | <ul style="list-style-type: none"> • Built-in 100 micron strainer stops particles before they enter the waterway • Waterways are lead-free in materials & construction • Flexible one-piece water saver bubbler infused with silver-based antimicrobial additive • Stainless steel top and heavy duty galvanized steel frame • Contactless activation on VersaFiller bottle filler • Contactless infrared sensor activation on each fountain operate independently of each other • VersaFilter III located in top bottle filler for easy filter replacement with Tilt 'N Tether • External access to stream height adjustment on lower Versacooler fountain • External access to thermostat with tool activated OFF position • Includes integral self-scouring waste drain • Built-in filter monitor and bottle counter • Universal design: high right or high left | |
| Filtration: | VersaFilter III is Certified to NSF/ANSI 42 and 53 for lead, Particulate Class I, chlorine, taste and odor reduction to 4,750 gallons | |
| Power: | 115 Volts, 60 Hz | |
| Activation By: | Contactless Sensor on Bottle Filler and Fountains | |
| Mounting Type: | Wall Mounted | |
| Chilling Option: | 8.0 gph* | Non-refrigerated |
| Full Load Amps: | 5.0 amps | 0.4 amps |
| Rated Watts: | 500 | 20 |
| Approx. Net Weight | 87 | 56 |
| Installation Location: | Indoor | |

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting brackets
- Removable side and front panels provide easy access for installation.

Finishes

- Standard: Greystone powder coat on galvanized steel
- Sandstone powder coat on galvanized steel; stainless steel (at additional cost)

Options

- One piece chrome plated brass bubbler (036700-001)

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

WARNING:



Cancer and Reproductive Harm
www.P65Warnings.ca.gov



*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Specifications subject to change without notice

OASIS CONTACTLESS BI-LEVEL VERSACOOLER® II WITH CONTACTLESS VERSAFILLER® WITH VERSAFILTER™ III

