



We Know Water.

**CONTACTLESS BI-LEVEL
VERSACOOLER® II, FILTERED**

- **PGF8ACSLTT**
- **PGFACSLTT**

Suggested Specification

Model PGF8ACSLTT shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGFACSLTT is a non-refrigerated drinking fountain and delivers ambient water. Each fountain shall have independent activation using contactless infrared sensor to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be greystone on galvanized steel or sandstone powder coated or brushed stainless steel. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



	PGF8ACSLTT	PGFACSLTT
Features:	<ul style="list-style-type: none"> • Universal design: high right or high left • Built-in 100 micron strainer stops particles before they enter the waterway • Waterways are lead-free in materials & construction • Flexible and one-piece water saver bubbler infused with silver-based antimicrobial additive • Stainless steel top and heavy duty galvanized steel frame • High efficiency cooling system • Contactless Infrared sensor activation on both fountains • Includes integral self-scouring waste drain • External access to stream height adjustment on fountains • External access to thermostat with tool activated OFF position 	
Filtration:	VersaFilter III is Certified to NSF/ANSI 42 and 53 for lead, cyst, Particulate Class I, chlorine, taste and odor reduction to 4,750 gallons	
Power:	115 Volts, 60 Hz	
Activation By:	Contactless Activation	
Mounting Type:	Wall Mounted	
Chilling Option:	8.0 gph*	Non-Refrigerated
Full Load Amps	5.0 amps	0.4 amps
Rated Watts	500	20
Approx. Net Weight	65 lbs	38 lbs
Installation Location:	Indoor	

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Finishes

- Standard: Greystone powder coat on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

Options

- Push handle glass fillers (029603-004)
- One piece chrome plated brass bubbler (036700-001)

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov

*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature



Specifications subject to change without notice

