

# VERSACOOLER™ SINGLE DRINKING FOUNTAIN, WITH VANDAL RESISTANT BUBBLER, NON-REFRIGERATED & ELECTRONIC BOTTLE FILLER, VERSAFILTER III FILTER

# **MODEL PGFEBF-BRB-FVF**

#### Suggested Specification

Features:

Filtration System:

Installation

Location:

Model PGFEBF-BRB-FVF is a non-refrigerated model and delivers ambient drinking water. Shall include the VersaFiller® with contactless activation and laminar flow; lower unit shall have four push pads to activate the manual flow of water for the cooler. Bottle Filler alcove and cabinet finish shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards, and comply with NSF/ANSI 61 and NSF/ANSI 372.

- Built-in 100 micron strainer stops particles before they enter the waterway
- Waterways are lead-free in materials & construction
- Stainless steel top and heavy duty galvanized steel frame
- Contactless activation bottle filler with programmable auto shut off
- Flexible one-piece water saver bubbler infused with silver-based antimicrobial additive
- · Includes integral self-scouring waste drain
- External access to stream height adjustment on lower Versacooler fountain
- Filter located in top bottle filler for easy filter replacement with Tilt 'N Tether
- · Built-in filter monitor and bottle counter
- Logos permanently formed into the alcove and stainless steel wrapper


OASIS VersaFilter III, certified to NSF/ANSI 42, 53, 372

and 401 for lead, Particulate Class I, chlorine, taste,

Indoor

LED lighted alcove

	odor and microplastics reduction to 4,750 gallons.
Power:	115 Volts, 60 Hz
Activation By:	Contactless Sensor on Bottle Filler and Manual Activation on Fountain
Mounting Type:	Wall Mounted
Chilling Option:	Non-refrigerated
Full Load Amps	0.2 amps
Rated Watts	11
Approx. Net Weight	33 lbs





#### Ships in one box.

- Installation
   Prior to rough-in consult with local, state and federal codes for proper mounting height
- · Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation.

#### **Finishes**

- · Standard: Greystone powder coat on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

### **Limited 1-Year Warranty**

(Continental limits of the United States and Canada)
One year on bottle fillers and electrical components. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

#### **Export Warranty**

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

### **Certifications/Compliance**

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These waters coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



#### WARNING:

Cancer and Reproductive Harm www.P65Warnings.ca.gov









Specifications subject to change without notice



#### **Accessories**



# **OASIS VersaFilter III Replacement Cartridge**

OASIS Item #041145-001

Certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



### Cane apron

Greystone Finish, OASIS Item # 035174-001 Sandstone Finish, OASIS Item # 035174-002 Stainless Steel Finish, OASIS Item #035174-003

ADA Compliant Apron is needed when water cooler is not installed in an alcove or with right and left wing walls. OASIS Apron is to provide the mandatory 27" to floor ADA requirement.



View all filters and accessories



## **MODEL PGFEBF-BRB-FVF**

