OASIS®

VERSACOOLER™ BI-LEVEL CONTACTLESS DRINKING FOUNTAIN, NON-REFRIGERATED & ELECTRONIC BOTTLE FILLER, TOTAL PFAS FILTER
MODEL PGFEBFSLTT-FPF

Suggested Specification

Model PGFEBFSLTT-FPF a non-refrigerated model and delivers ambient drinking water. Shall include the VersaFiller® with contactless activation and laminar flow; each fountain shall have independent activation using contactless infrared sensor to activate the flow of water. Bottle Filler alcove and cabinet finish shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards, and comply with NSF/ANSI 61 and NSF/ANSI 372.

Features:	· Universal design: high right or high left
	· Built-in 100 micron strainer stops particles before they enter the waterway
	· Waterways are lead-free in materials & construction
	· Stainless steel top and heavy duty galvanized steel frame
	· Contactless activation bottle filler with programmable auto shut off
	· Flexible one-piece water saver bubbler infused with silver-based antimicrobial additive
	· Includes integral self-scouring waste drain
	· External access to stream height adjustment on lower Versacooler fountain
	· Filter located in top bottle filler for easy filter replacement with Tilt 'N Tether
	· Built-in filter monitor and bottle counter
	· Logos permanently formed into the alcove and stainless steel wrapper
	· LED lighted alcove

Filtration System:	OASIS Total PFAS, certified to NSF/ANSI 42, 53, 372 and 401 for chlorine, taste, odor, particulate class 1, lead, cysts, Total PFAS, and microplastics reduction to 1,100 gallons.
Power:	115 Volts, 60 Hz
Activation By:	Contactless Sensor on Bottle Filler and Fountains
Mounting Type:	Wall Mounted
Chilling Option:	Non-Refrigerated
Full Load Amps	0.4 amps
Rated Watts	20
Approx. Net Weight	50 lbs
Installation Location:	Indoor

Ships in one box.

Installation
· Prior to rough-in consult with local, state and federal codes for proper mounting height
· Shipped with complete instructions and wall mounting bracket
· Removable side and front panels provide easy access for installation.

Finishes
· Standard: Greystone powder coat on galvanized steel
· Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

Limited 1-Year Warranty
(Continental limits of the United States and Canada)
One year on bottle fillers and electrical components. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty
One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance
· Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
· Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
· These waters coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

MODEL:_____ QTY:_____

PROJECT:_____

CONTACT:_____

NOTES:_____

APPROVAL:_____ DATE:_____

Specifications subject to change without notice

Accessories

OASIS Total PFAS Replacement Cartridge
OASIS Item #041668-001

- Certified to NSF/ANSI 42, 53, 372 and 401 for chlorine, taste, odor, particulate class 1, lead, cysts, Total PFAS, and microplastics reduction to 1,100 gallons.

One piece chrome plated brass bubbler
OASIS Item #036700-001

View all filters and accessories

NOTES:
1. TRAP, STOP VALVE AND ELECTRICAL OUTLET NOT FURNISHED.
2. ALLOW 4 INCHES [102 MM] MIN. PER SIDE FOR VENTILATION. PER SIDE FOR VENTILATION.
3. RECOMMENDED ADULT BARRIER FREE HEIGHT INSTALLATIONS SHOWN. REDUCE HEIGHT BY 3 INCHES FOR INSTALLATIONS USED PRIMARILY BY CHILDREN AGES 12 AND YOUNGER. UNIT SHALL ALSO HAVE A MINIMUM CLEAR FLOOR SPACE 30[760] BY 48[1220]. ADJUST VERTICAL DIMENSIONS AS REQUIRED TO COMPLY WITH FEDERAL, STATE, AND LOCAL CODES.
4. 115v GROUNDED NORTH AMERICAN DUPLEX RECEPTACLE REQUIRED. THIS DRINKING WATER COOLER IS INTENDED TO BE CONNECTED TO A 20A MINIMUM GROUND FAULT CIRCUIT INTERRUPTING (GFCI) DEVICE TO MEET UL REQUIREMENTS.
5. ALL DIMENSIONS ARE IN INCHES. DIMENSIONS IN BRACKETS [ ] ARE IN MILLIMETERS.

ROUGHING-IN AND DIMENSIONAL DRAWING

THIRD ANGLE PROJECTION

T15 DRIVE SIZE TORX HEAD SCREWS

1¼ O.D. TAILPIECE

WALL LINE

PUSH BUTTON

PGV(8)EBFSL
PG(8)EBFSL

PUSH PAD COOLER & FOUNTAIN
PG(8)EBFSL, PG(8)FEBFSL

WATER COOLER

WATER FOUNTAIN

¼[6] HANGER MOUNTING HOLE, 2 PLCS

5/16 [8] HANGER MOUNTING HOLES, 4 PLCS

AIR FLOW

¼[6] MOUNTING HOLES 8 PLCS

ELECTRICAL OUTLET OPTIMUM LOCATION (SEE NOTE 4)

WATER SUPPLY OPTIMUM LOCATION STUB OUT 1[25]

TOUCH FREE SENSOR UNDER NOSE

TOUCH FREE SENSOR UNDER NOSE

PUSH PAD

PG(8)EBFSLT
PG(8)FEBFSLT

PG(8)EBFSLTM
PG(8)FEBFSLTM

⅜ O.D. WATER INLET WITH STRAINER

FILTER LOCATION

CONNECT COOLER REMOTE OUTLET TO FOUNTAIN WATER INLET WITH SUPPLIED FITTING

1¼ IPS WASTE OPTIMUM LOCATION STUB OUT 1[25]

FLOOR LINE

4½ [114]
*38 3/16 [970]
18 29/32 [480]
6 [152]
6 7/32 [158]
7 3/8 [187]
8¼ [209]
*13 9/32 [337]
*21¼ [540]
*27 [686]
*32 7/16 [824] ORIFICE
*37 1/8 [943]
*51 3/32 [1298]

*35 5/16 [897]
1½ [38]
14 1/8 [359]
*24 1/16 [611]
12¾ [324]
7 23/32 [196]
2¼ [57]
17 5/8 [448]
6⅜ [162]
15 7/16 [392]
1 [25]
7 [178]
4 [102]
⅜ [13]
½ [13]
16½ [419]
25/32 [20]
*17 [432]
*18 1/16 [459]
*21¼ [540]
*29 5/16 [744]
33⅜ [849]
7/8 [22]
7/16 [11] TYP
35¼ [895]
18⅝ [472]
16¼ [413]