



14 GAUGE, VANDAL RESISTANT SPLIT LEVEL DRINKING FOUNTAIN & ELECTRONIC BOTTLE FILLER, WITH TOTAL PFAS FILTER MODEL PGV8FEBFSL-14G-FPF

Suggested Specification

Model PGV8FEBFSL-14G-FPF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing*. Shall include the VersaFiller with contactless activation and laminar flow. Bottle filler alcove and cabinet finish shall be stainless steel. Key VersaFiller components contain Freshield, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Cabinet & basin shall be 14 gauge stainless steel, with a heavy duty galvanized frame, with galvanized steel screens to prevent objects from being inserted into ventilation panels or underside of unit. Each fountain shall include a single vandal resistant push button to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. One-Piece low flow vandal resistant chrome plated solid construction bubbler keyed into place to prevent vandalism. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards, and comply with NSF/ANSI 61 and NSF/ANSI 372.

Features:	<ul style="list-style-type: none">• Universal design: high right or high left• Built-in 100 micron strainer stops particles before they enter the waterway• Waterways are lead-free in materials & construction• 14 gauge stainless steel construction• One-piece vandal resistant water saver bubbler keyed into position• Vandal resistant fasteners• Galvanized steel louver and bottom screens• High efficiency cooling system• Vandal resistant mechanical front push button• Contactless activation bottle filler with programmable auto shut off• Ample space within the bottle filler cabinet to add filtration, including all OASIS filters• Includes integral self-scouring waste drain• Stream height adjustment• Built-in filter monitor and bottle counter• Logos permanently formed into the alcove and stainless steel wrapper• LED lighted alcove• Mechanical activation on the fountain
	Filtration System: OASIS Total PFAS, certified to NSF/ANSI 42, 53, 372 and 401 for chlorine, taste, odor, particulate class 1, lead, cysts, Total PFAS, and microplastics reduction to 1,100 gallons.
Power:	115 Volts, 60 Hz
Activation By:	Contactless Sensor on Bottle Filler and Manual Activation on Fountains
Mounting Type:	Wall Mounted
Chilling Option:	8.0 gph*
Full Load Amps:	5.5 amps
Rated Watts:	550
Approx. Net Weight	92 lbs.
Installation Location:	Indoor



Ships in 2 boxes.

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting brackets
- Removable side and front panels provide easy access for installation.

Finishes

- Standard cabinet finish: Stainless steel

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system. Bottle fillers, fountains, and electrical components are warranted for 12 months. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



MODEL: _____ QTY: _____

PROJECT: _____

CONTACT: _____

NOTES: _____

APPROVAL: _____ DATE: _____

*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Specifications subject to change without notice



14 GAUGE, VANDAL RESISTANT SPLIT LEVEL DRINKING FOUNTAIN
& ELECTRONIC BOTTLE FILLER, WITH TOTAL PFAS FILTER
MODEL PGV8FEBFSL-14G-FPF

Accessories



OASIS Total PFAS Replacement Cartridge

OASIS Item #041668-001

- Certified to NSF/ANSI 42, 53, 372 and 401 for chlorine, taste, odor, particulate class 1, lead, cysts, Total PFAS, and microplastics reduction to 1,100 gallons.



[View all filters and accessories](#)

