



14 GAUGE VERSACOOLER™ VANDAL RESISTANT BI-LEVEL DRINKING FOUNTAIN, VANDAL RESISTANT BUBBLER, REFRIGERATED & MECHANICAL BOTTLE FILLER, VERSAFILTER III FILTER

MODEL PGV8FSBFSL-14G-FVF

Suggested Specification

Model PGV8FSBFSL-14G-FVF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing*. Shall include the VersaFiller® Sports Bottle Filler with independent push button manual activation and laminar flow Bottle filler alcove and cabinet finish shall be stainless steel.

Key VersaFiller components contain Freshield, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Cabinet & basin shall be 14 gauge stainless steel, with a heavy duty galvanized frame, with galvanized steel screens to prevent objects from being inserted into ventilation panels or underside of unit. Each fountain shall include a single vandal resistant push button to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. One-Piece low flow vandal resistant chrome plated solid construction bubbler keyed into place to prevent vandalism. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards, and comply with NSF/ANSI 61 and NSF/ANSI 372.

Features:	<ul style="list-style-type: none">• Universal design: high right or high left• Built-in 100 micron strainer stops particles before they enter the waterway• Waterways are lead-free in materials & construction• 14 gauge stainless steel construction• One-piece vandal resistant water saver bubbler keyed into position• Vandal resistant fasteners
	<ul style="list-style-type: none">• Galvanized steel louver and bottom screens• High efficiency cooling system• Vandal resistant mechanical front push button• Manual activation bottle filler and fountain• Filter located in top bottle filler for easy filter replacement with Tilt 'N Tether• Includes integral self-scouring waste drain• Stream height adjustment• Logos permanently formed into the alcove and stainless steel wrapper
Filtration System:	OASIS VersaFilter III, certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.
Power:	115 Volts, 60 Hz
Activation By:	Independent Manual Activation on Bottle Filler and Fountain
Mounting Type:	Wall Mounted
Chilling Option:	8.0 gph*
Full Load Amps:	5.5 amps
Rated Watts:	550
Approx. Net Weight	91 lbs.
Installation Location:	Indoor



Ships in 2 boxes.

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting brackets
- Removable side and front panels provide easy access for installation.

Finishes

- Standard cabinet finish: Stainless steel

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system. Bottle fillers, fountains, and electrical components are warranted for 12 months. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:

Cancer and Reproductive Harm
www.P65Warnings.ca.gov



MODEL: _____ QTY: _____

PROJECT: _____

CONTACT: _____

NOTES: _____

APPROVAL: _____ DATE: _____

*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Specifications subject to change without notice



14 GAUGE VERSACOOLER™ VANDAL RESISTANT BI-LEVEL DRINKING FOUNTAIN, VANDAL RESISTANT BUBBLER, REFRIGERATED & MECHANICAL BOTTLE FILLER, VERSAFILTER III FILTER

MODEL PGV8FSBFSL-14G-FVF

Accessories



OASIS VersaFilter III Replacement Cartridge

OASIS Item #041145-001

- Certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



[View all filters and accessories](#)



14 GAUGE VERSACOOLER™ VANDAL RESISTANT BI-LEVEL DRINKING FOUNTAIN, VANDAL RESISTANT BUBBLER, REFRIGERATED & MECHANICAL BOTTLE FILLER, VERSAFILTER III FILTER

MODEL PGV8FSBFSL-14G-FVF

NOTES:

1. TRAP, STOP VALVE AND ELECTRICAL OUTLET NOT FURNISHED.
2. ALLOW 4 INCHES (102MM) MIN. PER SIDE FOR VENTILATION.
- *3. RECOMMENDED ADULT BARRIER FREE HEIGHT INSTALLATION SHOWN. REDUCE HEIGHT BY 3 INCHES FOR INSTALLATIONS USED PRIMARILY BY CHILDREN AGES 12 AND YOUNGER. UNIT SHALL ALSO HAVE A MINIMUM CLEAR FLOOR SPACE 307/60 BY 481/220. ADJUST VERTICAL DIMENSIONS AS REQ'D TO COMPLY WITH FEDERAL, STATE, AND LOCAL CODES.
4. 115V GROUND NORTH AMERICAN DUPLEX RECEPTICAL REQUIRED. THIS DRINKING WATER COOLER IS INTENDED TO BE CONNECTED TO A 20A MINIMUM GROUND FAULT CIRCUIT INTERRUPTING (GFCI) DEVICE TO MEET ALL REQUIREMENTS.
5. ALL DIMENSIONS ARE IN INCHES. DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS.
6. ROUGH-IN DRAWING IS SHOWN WITH A PGV8AC UNIT IN ORDER TO SHOW THE PROPER HEIGHT OF THE UNIT WHEN RETROFITTED TO THE PARENT UNIT AND HEIGHT FROM THE FLOOR IN ORDER TO COMPLY WITH ADA STANDARDS. THE PGV8AC UNIT IS NOT INCLUDED WITH THE PURCHASE OF THE PGV8FSL.

