



SINGLE VANDAL RESISTANT FOUNTAIN, REFRIGERATED WITH VANDAL RESISTANT BUBBLER  
& VANDAL RESISTANT ELECTRO-MECHANICAL BOTTLE FILLER, VERSAFILTER III FILTER

## MODEL PGV8FSVBF-BRB-FVF

### Suggested Specification

Model PGV8FSVBF-BRB-FVF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Shall include a vandal resistant bottle filler with vandal resistant electro-mechanical push button activation and laminar flow, fountain shall have a single vandal resistant push button to activate the manual flow of water for the cooler. All bottle filler exterior cabinet and drip tray shall be 18 gauge stainless steel. Key bottle filler components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Vandal Resistant water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. One-piece vandal resistant metal bubbler keyed into place to prevent vandalism. Cabinet finish shall be brushed stainless steel. Cabinet shall have perforated galvanized steel screens to prevent objects from being inserted into the cooler. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

<b>Features:</b>	<ul style="list-style-type: none"><li>• Built-in 100 micron strainer stops particles before they enter the waterway</li><li>• Waterways are lead-free in materials &amp; construction</li><li>• Vandal resistant metal water saver bubbler</li><li>• Vandal resistant manual solenoid activation push button on the bottle filler and vandal resistant push button on fountain</li><li>• Vandal resistant fasteners on bottle filler and fountain</li><li>• Galvanized steel louver and bottom screens</li><li>• Stainless steel top and heavy duty galvanized steel frame</li><li>• High efficiency cooling system</li><li>• Includes integral self-scouring waste drain</li><li>• Filter located in top bottle filler for easy filter replacement with Tilt 'N Tether</li><li>• External access to thermostat with tool activated OFF position</li><li>• Built-in filter monitor and bottle counter</li><li>• Logos permanently formed into stainless steel wrapper</li></ul>
	<b>Filtration System:</b> OASIS VersaFilter III, certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.

<b>Power:</b>	115 Volts, 60 Hz
<b>Activation By:</b>	Independent Manual Activation on Bottle Filler and Fountain
<b>Mounting Type:</b>	Wall Mounted
<b>Chilling Option:</b>	8.0 gph*
<b>Full Load Amps</b>	5.5 amps
<b>Rated Watts</b>	550
<b>Approx. Net Weight</b>	64 lbs
<b>Installation Location:</b>	Indoor

MODEL: \_\_\_\_\_ QTY: \_\_\_\_\_

PROJECT: \_\_\_\_\_

CONTACT: \_\_\_\_\_

NOTES: \_\_\_\_\_

APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_



**Ships in one box.**

### Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

### Finishes

- Standard cabinet finish: Stainless steel

### Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system. Bottle fillers, fountains, and electrical components are warranted for 12 months. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

### Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

### Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature



**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



Specifications subject to change without notice



SINGLE VANDAL RESISTANT FOUNTAIN, REFRIGERATED WITH VANDAL RESISTANT BUBBLER  
& VANDAL RESISTANT ELECTRO-MECHANICAL BOTTLE FILLER, VERSAFILTER III FILTER

**MODEL PGV8FSVBF-BRB-FVF**

## Accessories



### OASIS VersaFilter III Replacement Cartridge

OASIS Item #041145-001

- Certified to NSF/ANSI 42, 53, 372 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



### Cane apron, Stainless Steel

OASIS Item #035174-003

- ADA Compliant Apron is needed when water cooler is not installed in an alcove or with right and left wing walls. OASIS Apron is to provide the mandatory 27" to floor ADA requirement.



[View all filters and accessories](#)



SINGLE VANDAL RESISTANT FOUNTAIN, REFRIGERATED WITH VANDAL RESISTANT BUBBLER  
& VANDAL RESISTANT ELECTRO-MECHANICAL BOTTLE FILLER, VERSAFILTER III FILTER

## MODEL PGV8FSVBF-BRB-FVF

