



We Know Water.

OUTDOOR RATED 14 GAUGE VANDAL RESISTANT BARRIER-FREE VERSACOOLER® II

• PGVD8AC-14G • PGVDAC-14G

Suggested Specification

Model PGVD8AC-14G shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGVDAC-14G is a non-refrigerated fountain and delivers ambient water. Cabinet and top basin shall be 14 gauge stainless steel, with a heavy duty galvanized frame, with galvanized steel screens to prevent objects from being inserted into ventilation panels or under-side of unit. Unit shall include a single vandal resistant push button to activate the flow of water. Water saver bubbler reduces waste water by 50% and shall operate between 20 and 100 PSI. One-piece low flow vandal resistant chrome plated solid construction metal bubbler keyed into place to prevent vandalism. Cooling system shall use R-134a refrigerant, shall comply with ANSI A117.1 and ADA, listed by UL to Canadian Standards, and NSF/ANSI 61 and NSF/ANSI 372.



	PGVD8AC-14G	PGVDAC-14G
Features:	<ul style="list-style-type: none">Built-in 100 micron strainer stops particles before they enter the waterwayWaterways are Lead-Free in materials & construction14 gauge Stainless Steel constructionVandal resistant water saver bubblerVandal resistant mechanical front push buttonsOne-piece vandal resistant bubbler keyed into positionVandal resistant fastenersGalvanized steel louver and bottom screensHigh efficiency cooling systemStream height adjustmentRated for Indoor and OutdoorIncludes integral self-scouring waste drain	
Filtration:	Option to add filtration	
Power:	115 Volts, 60 Hz	
Activation By:	Manual Activation on Fountain	
Mounting Type:	Wall Mounted	
Chilling Option:	8.0 gph*	Non-Refrigerated
Full Load Amps:	5.5 amps	0 amps
Rated Watts:	550	0
Approx. Net Weight:	65 bs	35 lbs
Installation Location:	Indoor/Outdoor	

When used or stored in non-temperature controlled environments, the unit must be adequately winterized and/or protected from extreme heat to prevent damage.

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Finishes

- Standard cabinet finish: Stainless steel

Options

- OASIS Versafilter III Kit 041253-001**

Limited 5-Year Warranty

(Continental limits of the United States and Canada)
Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Specifications subject to change without notice
**Filters are not rated for outdoor use

OUTDOOR RATED 14 GAUGE VANDAL RESISTANT BARRIER-FREE VERSACOOLER® II

