



# We Know Water.

## OUTDOOR RATED 14 GAUGE VANDAL RESISTANT UNIVERSAL BARRIER-FREE VERSACOOLER® II

• PGVD8ACSL-14G • PGVDACSL-14G

### Suggested Specification

Model PGVD8ACSL-14G shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGVDACSL-14G is a non-refrigerated fountain and delivers ambient water. Cabinet and top basin shall be 14 gauge stainless steel, with a heavy duty galvanized frame, with galvanized steel screens to prevent objects from being inserted into ventilation panels or under-side of unit. Unit shall include a single vandal resistant push button to activate the flow of water. Water saver bubbler reduces waste water by 50% and shall operate between 20 and 100 PSI. One-piece low flow vandal resistant chrome plated solid construction metal bubbler keyed into place to prevent vandalism. Cooling system shall use R-134a refrigerant, shall comply with ANSI A117.1 and ADA, listed by UL to Canadian Standards, and NSF/ANSI 61 and NSF/ANSI 372.



	PGVD8ACSL-14G	PGVDACSL-14G
<b>Features:</b>	<ul style="list-style-type: none"><li>Built-in 100 micron strainer stops particles before they enter the waterway</li><li>Waterways are Lead-Free in materials &amp; construction</li><li>14 gauge Stainless Steel construction</li><li>Vandal resistant water saver bubbler</li><li>Vandal resistant mechanical front push buttons</li><li>One-piece vandal resistant bubbler keyed into position</li><li>Vandal resistant fasteners</li><li>Galvanized steel louver and bottom screens</li><li>High efficiency cooling system</li><li>Stream height adjustment</li><li>Rated for Indoor and Outdoor</li><li>Includes integral self-scouring waste drain</li><li>Universal design: high right or high left</li></ul>	
<b>Filtration:</b>	Option to add filtration	
<b>Power:</b>	115 Volts, 60 Hz	
<b>Activation By:</b>	Manual Activation on Fountains.	
<b>Mounting Type:</b>	Wall Mounted	
<b>Chilling Option:</b>	8.0 gph*	Non-Refrigerated
<b>Full Load Amps:</b>	5.5 amps	0 amps
<b>Rated Watts:</b>	550	0
<b>Approx. Net Weight:</b>	100 lbs	70 lbs
<b>Installation Location:</b>	Indoor/Outdoor	

When used or stored in non-temperature controlled environments, the unit must be adequately winterized and/or protected from extreme heat to prevent damage.

### Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

### Finishes

- Standard cabinet finish: Stainless steel

### Options

- OASIS VersaFilter Systems\*\*

### Limited 5-Year Warranty

(Continental limits of the United States and Canada)  
Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

### Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

### Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Specifications subject to change without notice  
\*\*Filters are not rated for outdoor use

# OUTDOOR RATED 14 GAUGE VANDAL RESISTANT UNIVERSAL BARRIER-FREE VERSACOOLER® II

