



Suggested Specification

Model PGVDF8AC shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Shall include a single vandal resistant push button to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler reduces waste water by 50% and shall operate between 20 and 100 PSI. One-piece vandal resistant metal bubbler keyed into place to prevent vandalism. Cabinet finish shall be brushed stainless steel. Cabinet shall have perforated galvanized steel screens to prevent objects from being inserted into the cooler. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

Features:	<ul style="list-style-type: none">• Built-in 100 micron strainer stops particles before they enter the waterway• Waterways are Lead-Free in materials & construction• Vandal resistant water saver bubbler• Vandal resistant mechanical front push button• One-piece vandal resistant bubbler keyed into position
	<ul style="list-style-type: none">• Vandal resistant fasteners• Galvanized steel louver and bottom screens• Stainless steel top and heavy duty galvanized steel frame• Stream height adjustment• Includes integral self-scouring waste drain• High efficiency cooling system• Rated for Indoor and Outdoor
Filtration:	OASIS Outdoor Filter
Power:	115 Volts, 60 Hz
Activation By:	Manual Activation on Fountain
Mounting Type:	Wall Mounted
Chilling Option:	8.0 gph*
Full Load Amps	5.5 amps
Rated Watts	550
Approx. Net Weight	51 lbs
Installation Location:	Indoor/Outdoor

SINGLE OUTDOOR VANDAL RESISTANT FOUNTAIN, REFRIGERATED, FILTERED MODEL PGVDF8AC



Ships in one box.

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Finishes

- Standard cabinet finish: Stainless steel

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system. Bottle fillers, fountains, and electrical components are warranted for 12 months. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

When used or stored in non-temperature controlled environments, the unit must be adequately winterized and/or protected from extreme heat to prevent damage.



WARNING:

Cancer and Reproductive Harm
www.P65Warnings.ca.gov



Specifications subject to change without notice

MODEL: _____ QTY: _____

PROJECT: _____

CONTACT: _____

NOTES: _____

APPROVAL: _____ DATE: _____



SINGLE OUTDOOR VANDAL RESISTANT
FOUNTAIN, REFRIGERATED, FILTERED
MODEL PGVDF8AC

Accessories



OASIS Outdoor Replacement Cartridge

OASIS Item #041667-001

- Certified to NSF/ANSI 42, 53 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



[View all filters and accessories](#)



SINGLE OUTDOOR VANDAL RESISTANT
FOUNTAIN, REFRIGERATED, FILTERED
MODEL PGVDF8AC

