



# VERSACOOLER™ VANDAL RESISTANT BI-LEVEL DRINKING FOUNTAIN, REFRIGERATED, FILTERED MODEL PGVF8ACSL

## Suggested Specification

Model PGVF8ACSL shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Shall include a single vandal resistant push button on each fountain to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be brushed stainless steel. Cabinet shall have perforated galvanized steel screens to prevent objects from being inserted into the cooler. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

<b>Features:</b>	• Universal design: high right or high left
	• Built-in 100 micron strainer stops particles before they enter the waterway
	• Waterways are lead-free in materials & construction
	• Vandal resistant water saver bubbler infused with silver-based antimicrobial additive
	• Vandal resistant fasteners
	• Galvanized steel louver and bottom screens
	• Stainless steel top and heavy duty galvanized steel frame
	• High efficiency cooling system
	• Vandal resistant mechanical front push button
	• Includes integral self-scouring waste drain
<b>Choice of Filtration System:</b>	• External access to stream height adjustment on lower VersaCooler fountain
	• External access to thermostat with tool activated OFF position
	• Mechanical activation
<b>Power:</b>	• OASIS VersaFilter III
	• OASIS Total PFAS Filter
	• OASIS Pharmaceutical Filter
<hr/>	
<b>Power:</b>	115 Volts, 60 Hz
<hr/>	
<b>Activation By:</b>	Manual activation
<hr/>	
<b>Mounting Type:</b>	Wall Mounted
<hr/>	
<b>Chilling Option:</b>	8.0 gph*
<hr/>	
<b>Full Load Amps</b>	5.0 amps
<hr/>	
<b>Rated Watts</b>	500
<hr/>	
<b>Approx. Net Weight</b>	69 lbs
<hr/>	
<b>Installation Location:</b>	Indoor



**Ships in one box.**

## Installation

- Prior to roughing in, consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

## Finishes

- Standard cabinet finish: Stainless steel

## Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system. Bottle fillers, fountains, and electrical components are warranted for 12 months. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

## Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

## Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

MODEL: \_\_\_\_\_ QTY: \_\_\_\_\_  
PROJECT: \_\_\_\_\_  
CONTACT: \_\_\_\_\_  
NOTES: \_\_\_\_\_  
APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_



**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



Specifications subject to change without notice



# VERSACOOLER™ VANDAL RESISTANT BI-LEVEL DRINKING FOUNTAIN, REFRIGERATED, FILTERED **MODEL PGVF8ACSL**

## Accessories



### **OASIS VersaFilter III Replacement Cartridge**

OASIS Item #041145-001

- Certified to NSF/ANSI 42, 53 and 401 for lead, Particulate Class I, chlorine, taste, odor and microplastics reduction to 4,750 gallons.



### **OASIS Total PFAS Replacement Cartridge**

OASIS Item #041668-001

- Certified to NSF/ANSI 42, 53 and 401 for chlorine, taste, odor, particulate class I, lead, cysts, Total PFAS, and microplastics reduction to 1,100 gallons.



### **OASIS Pharmaceutical Replacement Cartridge**

OASIS Item #041670-001

- Certified to NSF/ANSI 42, 53 and 401 for chlorine, taste, odor, particulate class I, lead, cysts, Atenolol, Bisphenol A, Carbamazepine, DEET (diethyltoluamide), Estrone, Ibuprofen, Meprobamate, Metolachlor, Naproxen, Nonyl phenol, Phenytoin and Trimethoprim, and microplastics reduction to 725 gallons.



### **One piece chrome plated brass bubbler**

OASIS Item #036700-001



[View all filters and accessories](#)

