OSIS

VERSAFILLER® CONTACTLESS RETROFIT BOTTLE FILLING STATION KIT, NON-REFRIGERATED, TOTAL PFAS FILTER MODEL PWFEBF-FPF

Suggested Specification

When retrofitted to either the PG8AC or P8AM, the PWFEBF-FPF bottle filler shall include contactless activation and laminar flow. VersaFiller alcove and cabinet shall be stainless steel. Key Versa-Filler components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Unit shall include filter monitor and bottle counter. When retrofitted to either the PG8AC or P8AM the VersaFiller models satisfy ANSI A117.1 and ADA requirements when properly installed. Units also meet guidelines for children's accessibility providing the floor to orifice height is 30 inches and proper clear floor space is provided for frontal approach. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

| Features: | Built-in 100 micron strainer stops particles before they enter the waterway | |
|---------------------------|--|--|
| | Waterways are lead-free in materials & construction | |
| | Heavy duty galvanized steel frame | |
| | Contactless activation bottle filler with programmable auto shut off | |
| | Access filtration through the top of the bottle filler for clean and easy replacement of filters with Tilt 'N Tether | |
| | • Built-in filter monitor and bottle counter | |
| | Logos permanently formed into the alcove and stainless steel wrapper | |
| | LED lighted alcove | |
| | Surface mount frame assembly | |
| Filtration System: | OASIS Total PFAS, certified to NSF/ANSI 42, 53, 372 and 401 for chlorine, taste, odor, particulate class 1, lead, cysts, Total PFAS, and microplastics reduction to 1,100 gallons. | |
| Power: | 115 Volts, 60 Hz | |
| Activation By: | Contactless Sensor | |
| Mounting Type: | Wall Mounted | |
| Chilling Option: | Utilizes existing refrigeration system if applicable | |
| Full Load Amps | 0.2 amps | |
| Rated Watts | 11 | |
| Approx. Net Weight | 19 lbs | |
| Installation Location: | Indoor | |

| MODEL: | QTY: |
|-----------|-------|
| PROJECT: | |
| CONTACT: | |
| NOTES: | |
| APPROVAL: | DATE: |



Ships in one box.

Installation

- The PWFEBF VersaFiller is designed to retrofit existing OASIS PG8AC and P8AM pressure cooler models. Units with optional glass fillers must have the glass filler disconnected and removed. Prior to rough-in consult with local, state, and federal codes for
- proper mounting height.
 Shipped with complete instructions and wall mounting brackets.

Finishes

· Standard cabinet finish: Stainless steel

Limited 1-Year Warranty

(Continental limits of the United States and Canada) One year on bottle fillers and electrical components. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These waters coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



Cancer and Reproductive Harm www.P65Warnings.ca.gov



Specifications subject to change without notice



VERSAFILLER® CONTACTLESS RETROFIT BOTTLE FILLING STATION KIT, NON-REFRIGERATED, TOTAL PFAS FILTER MODEL PWFEBF-FPF

Accessories



Elkay® Adapter Gasket

OASIS Item #041533-001

Elkay Adapter Gasket is necessary to complete installation if retroftting to an Elkay® fountain



OASIS Total PFAS Replacement Cartridge

OASIS Item #041668-001


Certified to NSF/ANSI 42, 53, 372 and 401 for chlorine, taste, odor, particulate class 1, lead, cysts, Total PFAS, and microplastics reduction to 1,100 gallons.



View all filters and accessories

OSIS

VERSAFILLER® CONTACTLESS RETROFIT BOTTLE FILLING STATION KIT, NON-REFRIGERATED, TOTAL PFAS FILTER MODEL PWFEBF-FPF



WATER WHERE YOU NEED IT. / OASIS INTERNATIONAL / 222 East Campus View Blvd., Columbus, OH 43235 / www.oasiscoolers.com / 1-800-646-2747 OASIS is a registered trademark of LVD Acquisition, LLC dba OASIS International, © 2024 LVD Acquisition | AS0467-F-2412