



# We Know Water.

## HANDS-FREE VERSAFILLER® WITH VERSAFILTER™ III RETROFIT KIT

### • PWFEFB

#### Suggested Specification

When retrofitted to either the PG8AC or P8AM, the PWFEFB bottle filler shall include contactless activation and laminar flow. Key VersaFiller components contain Freshshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Unit shall include filter monitor and bottle counter. VersaFiller cabinet finish is brushed stainless steel.

When retrofitted to either the PG8AC or P8AM the VersaFiller models satisfy ANSI A117.1 and ADA requirements when properly installed. Units also meet guidelines for children's accessibility providing the floor to orifice height is 30 inches and proper clear floor space is provided for frontal approach. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



<b>Features:</b>	<ul style="list-style-type: none"> <li>Waterways are lead-free in materials &amp; construction</li> <li>Contactless activation on VersaFiller bottle filler</li> <li>VersaFilter III located in top bottle filler for easy filter replacement with Tilt 'N Tether</li> <li>Integrated back-lit bottle counter</li> <li>Built in filter monitor</li> <li>Heavy duty galvanized steel frame</li> <li>Surface mount frame assembly</li> </ul>
<b>Filtration:</b>	VersaFilter III is Certified to NSF/ANSI 42 and 53 for lead, Particulate Class I, chlorine, taste and odor reduction to 4,750 gallons
<b>Power:</b>	115 Volts, 60 Hz
<b>Activation By:</b>	Contactless Sensor
<b>Mounting Type:</b>	Wall Mounted
<b>Chilling Option:</b>	Utilizes existing refrigeration system if applicable
<b>Full Load Amps:</b>	0.2
<b>Rated Watts:</b>	11
<b>Approx. Net Weight:</b>	12 lbs.
<b>Installation Location:</b>	Indoor

The PWFEFB VersaFiller is designed to retrofit existing OASIS PG8AC and P8AM pressure cooler models. Models that this unit will not retro to are the electric eye P8AC and P8AM units. Units with optional glass fillers must have the glass filler disconnected and removed.

#### Installation

- Prior to rough-in consult with local, state, and federal codes for proper mounting height.
- Shipped with complete instructions and wall mounting brackets.

#### Finishes

- VersaFiller cabinet finish is brushed stainless steel

#### Options

- Elkay Adapter Gasket 041114-001
- Sunroc/HAWS Adapter Gasket 036689-101

#### Limited 1-Year Warranty

(Continental limits of the United States and Canada)

One year on components parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

#### Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

#### Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



#### WARNING:

Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



Specifications subject to change without notice

# OASIS® PWFEFB VERSAFILLER WITH VERSAFILTER™ III RETROFIT KIT

