



FULLY-RECESSED WITH CUP FILLER

NFRD8CD, NFRD12CD

Suggested Specification

Model NFRD8CD shall deliver 8.0 gph of 50° F at 90° F ambient and 80° F inlet water. Model NFRD12CD shall deliver 12.0 gph of 50° F at 90° F ambient and 80° F inlet water. Model NFRD8CD and NFRD12CD have a push button on the front of the cabinet. Water flows as long as the button is depressed. Cabinet finish shall be brushed stainless steel. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1. Shall be listed by Underwriters' Laboratories to U.S. and Canadian standards and conform to European Union Directives.

Models

NFRD8CD delivers 8.0 gph of chilled drinking water when the mechanical push-button is depressed, water continues to flow as long as the button is depressed. Features a matching cup filler, cup dispenser and disposer.

NFRD12CD delivers 12.0 gph of chilled drinking water when the mechanical push-button is depressed, water continues to flow as long as the button is depressed. Features a matching cup filler, cup dispenser and disposer.

Standard Features

- > Waterways are Lead-Free in Materials & Construction
- > Stainless Steel Surfaces
- > Welded, Heavy-Gauge Steel Wall Mounting Frame
- > High-Efficiency Cooling Tank and Coil
- > Refrigerant R-134a
- > Product Certified to NSF/ANSI Standard 61, Annex G (AB1953)
- > Limited 5-year Warranty

Finishes

- > Standard Cabinet Finish: Stainless Steel
- > Optional finishes (at additional cost): Regency Bronze



Components in these water coolers are lead free as defined by the Safe Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Accessory

- > Glass/Carafe Filler (Factory Installed 030239-003)
- > Cup Dispenser Component

Installation

- > Prior to roughing-in consult with local, state, and federal codes for proper mounting height.
- > Shipped with complete instructions and wall mounting sleeve
- > Removable panels provide easy access for installation.

Limited 5-Year Warranty (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty: One year on sealed refrigeration system and most components parts. Four-year replacement contract on sealed refrigeration system. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Product Certified to NSF/ANSI Standard 61, Annex G (weighted average lead content of $\leq 0.25\%$) and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953).

Models covered by this specification complies with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards and conform to European Union Directives.



Certified to
NSF/ANSI 61/ Section 9

Model	50° F Drinking Water 90° F Ambient Air Temp*				115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Pre-Cooler	Hot'N Cold™ Model	Compr. HP	Full Load Amps	Rated Watts			
NFRD8CD**	8.0	8.0	No	No	1/4	4.8	550	Yes	Yes	167 Lbs.
NFRD12CD**	12.0	12.0	No	No	1/3	5.4	620	Yes	Yes	168 Lbs.

* Air Conditioning and Refrigeration Institute Standard Rating Condition 80° F inlet water temperature

** Special export models available, operable on 220-240 volts, 50 Hertz. UL, CBA and ARI certification not applicable

Specifications subject to change without notice

FRONT VIEW

Overall width: 24 [610]
 Overall height: 55 1/2 [1410]
 Wall opening width: 16 [406]
 Wall opening height: 24 [610]
 Mounting holes: 5/8 [8] DIA. 8 EACH SIDE
 Tailpiece: 1 1/4 O.D. [127]
 Hole for electrical connections: 7/8 [22] DIA.
 Water supply stub out: 3/4 [25] INCH
 Water outlet tube: 1/4 O.D. [1384]
 Cooling unit water inlet: 5/8 [136]
 Junction box: 6 1/2 [165]
 Cooling unit: 18 [457]
 Cradle mounting screws: 3/32 [848]
 Rear of cooler top: 10 1/3 [274]
 Wall opening: 7 1/8 [198]

SIDE VIEW

Overall depth: 4 [102]
 Wall sleeve supplied: 5/8 [8] DIA.
 Mounting holes: 5/8 [8] DIA. 8 EACH SIDE
 Tailpiece: 1 1/4 O.D. [127]
 Hole for electrical connections: 7/8 [22] DIA.
 Water supply stub out: 3/4 [25] INCH
 Water outlet tube: 1/4 O.D. [1384]
 Cooling unit water inlet: 5/8 [136]
 Junction box: 6 1/2 [165]
 Cooling unit: 18 [457]
 Cradle mounting screws: 3/32 [848]
 Rear of cooler top: 10 1/3 [274]
 Wall opening: 7 1/8 [198]

TOP VIEW

Overall width: 24 [610]
 Wall opening width: 16 [406]
 Wall opening height: 24 [610]
 Mounting holes: 5/8 [8] DIA. 8 EACH SIDE
 Tailpiece: 1 1/4 O.D. [127]
 Hole for electrical connections: 7/8 [22] DIA.
 Water supply stub out: 3/4 [25] INCH
 Water outlet tube: 1/4 O.D. [1384]
 Cooling unit water inlet: 5/8 [136]
 Junction box: 6 1/2 [165]
 Cooling unit: 18 [457]
 Cradle mounting screws: 3/32 [848]
 Rear of cooler top: 10 1/3 [274]
 Wall opening: 7 1/8 [198]

NOTES:

1. TRAP AND STOP VALVE NOT FURNISHED.
2. RECOMMENDED ADULT HEIGHT INSTALLATION SHOWN. ADJUST VERTICAL DIMENSIONS AS REQ'D TO COMPLY WITH FEDERAL, STATE, AND LOCAL CODES.
3. ALL DIMENSIONS ARE IN INCHES. DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS.
4. HANG TOP OVER FLANGE OF WALL SLEEVE.
5. FASTEN BOTTOM OF COOLER TOP WITH NUTS AND BOLTS PROVIDED. (2 OF EACH)
6. POSITION TOP FLANGE OF GRILLE BEHIND REAR OF COOLER TOP.
7. INSTALL (2) SCREWS TO FASTEN GRILLE TO WALL SLEEVE.