



Water Coolers

FULLY-RECESSED

NFRD8, NFRD12

Suggested Specification

Model NFRD8 shall deliver 8.0 gph of 50° F at 90° F ambient and 80° F inlet water. Model NFRD12 shall deliver 12.0 gph of 50° F at 90° F ambient and 80° F inlet water. Model NFRD8 and NFRD12 have a push button on the front of the cabinet. Water flows as long as the button is depressed. Cabinet finish shall be brushed stainless steel. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1. Shall be listed by Underwriters' Laboratories to U.S. and Canadian standards and conform to European Union Directives.

Models

NFRD8 delivers 8.0 gph of chilled drinking water when the mechanical push-button is depressed, water continues to flow as long as the button is depressed.

NFRD12 delivers 12.0 gph of chilled drinking water when the mechanical push-button is depressed, water continues to flow as long as the button is depressed.

Standard Features

- > Waterways are Lead-Free in Materials & Construction
- > Stainless Steel Surfaces
- > Welded, Heavy-Gauge Steel Wall Mounting Frame
- > High-Efficiency Cooling Tank and Coil
- > Refrigerant R-134a
- > Limited 5-year Warranty

Finishes

- > Standard Cabinet Finish: Stainless Steel
- > Optional finishes (at additional cost): Regency Bronze



Components in these water coolers are lead free as defined by the Safe Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Accessory

- > Glass/Carafe Filler (Factory Installed 030239-003)
- > Cup Dispenser Component

Installation

- > Prior to roughing-in consult with local, state, and federal codes for proper mounting height.
- > Shipped with complete instructions and wall mounting sleeve
- > Removable panels provide easy access for installation.

Limited 5-Year Warranty (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty: One year on sealed refrigeration system and most components parts. Four-year replacement contract on sealed refrigeration system. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Product Certified to NSF/ANSI Standard 61, Annex G (weighted average lead content of $\leq 0.25\%$) and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953).

Models covered by this specification complies with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards and conform to European Union Directives.



Certified to
NSF/ANSI 61/Section 9


Model	50° F Drinking Water 90° F Ambient Air Temp*				115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Pre-Cooler	Hot'N Cold™ Model	Compr. HP	Full Load Amps	Rated Watts			
NFRD8 **	8.0	8.0	No	No	1/4	4.8	550	Yes	Yes	92 Lbs.
NFRD12 **	12.0	12.0	No	No	1/3	5.4	620	Yes	Yes	96 Lbs.

* Air Conditioning and Refrigeration Institute Standard Rating Condition 80° F inlet water temperature

** Special export models available, operable on 220-240 volts, 50 Hertz. UL, CBA and ARI certification not applicable

Specifications subject to change without notice

SUNROC® FULLY-RECESSED WATER COOLER MODEL NFRD8, NFRD12



- NOTES:
1. TRAP AND STOP VALVE NOT FURNISHED.
 2. RECOMMENDED ADULT HEIGHT INSTALLATION SHOWN. ADJUST VERTICAL DIMENSIONS AS REQ'D TO COMPLY WITH FEDERAL, STATE, AND LOCAL CODES.
 3. ALL DIMENSIONS ARE IN INCHES. DIMENSIONS IN BRACKETS [] ARE IN MILLIMETERS.
 4. HANG TOP OVER FLANGE OF WALL SLEEVE
 5. FASTEN BOTTOM OF COOLER TOP WITH NUTS AND BOLTS PROVIDED (2 OF EACH)
 6. POSITION TOP FLANGE OF GRILL BEHIND REAR OF COLLAR TOP.
 7. INSTALL (2) SCREWS TO FASTEN GRILL TO WALL SLEEVE.

